



**MARCHER**<sup>®</sup>  
OFF-HIGHWAY TIRE SOLUTION



**CHANGE POWERING  
THE FUTURE**

**QINGDAO MARCHER RUBBER CO.,LTD**  
(Qingdao Qizhou Rubber Co.,Ltd.)

Add:22F Fulin Mansion No 87 Fuzhou Road,  
Qingdao China  
Tel: +86 532 85794112  
Fax: +86 532 85794260  
Web: www.marchertire.com  
E-mail: admin@marchertire.com

**DISTRIBUTED BY:**

**VISIT US:**



# COMPANY PROFILE

Headquartered in Qingdao of China, MARCHER is a leading manufacturer and player in the Off-Highway tire market.

Since the founding in 1998, MARCHER has achieved the factory consisting of over 93,000 square meters for production plant and 62,000 square meters for R & D department. And MARCHER can annually produce 50,000 radial OTR tires, 500,000 bias OTR & construction tires, 10,000 giant OTR tires, 100,000 radial agricultural tires, 1,000,000 bias agricultural and forestry tires, and 2,000,000 solid industrial tires.

All MARCHER tires are in full compliance with international manufacturing and management standards & regulations, including ISO9001, US DOT and the national CCC, European Directive REACH, ECE, etc. MARCHER tires have successfully been operated in over 100 countries & regions, and already proved by FMG & Rio Tinto in Australia, and Shenhua Group in China, etc.

With "All-for-Durable" and environmental-friendly design philosophy, MARCHER is offering the most integrated production line, for equipment in agricultural, construction and industrial events as well as earthmoving, port and mining, and gardening applications. Believing in particularity, honesty and friendship, MARCHER are always ready to make friends.

# CONTENTS

- OTR AND CONSTRUCTION TIRES ..... 01-16
- AGRICULTURAL TIRES ..... 17-26
- SOLID TIRES ..... 26-28

**PRODUCE QUALITY TIRE**  
**RUN ALL OVER THE WORLD**

# TIRE ON EQUIPMENT





### SKS L-2

- Applications: skid steer, aerial boom lift, scissor lift, compact tractor, front backhoe, 3-wheel forklift
- The ideal tire for loose surfaces and heavy-duty service
- The extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 30kmh	Inflation Pressure (kpa) 30kmh
5.70-12	4	4.50	14	TL	146	570	858	415
8	8	4.50	14	TL	146	570	850	550
23x8.50-12	8	71-55	12	TL	213	574	820	340
10	10	71-55	12	TL	213	574	1020	480
26x12.00-12	6	10.51-55	13	TL	307	648	1110	240
10	10	10.51-55	13	TL	307	648	1630	450
12	12	10.51-55	13	TL	307	648	1890	550
27x8.50-15	6	7JA	15	TL	218	681	1210	315
8	8	7JA	15	TL	218	681	1310	415
12	12	7JA	15	TL	218	681	1510	620
27x10.50-15	8	8LB	15.5	TL	259	699	1410	415
12	12	8LB	15.5	TL	259	699	1610	620
31x15.50-15	8	13LBx15	19	TL	391	792	1420	310
10	10	13LBx15	19	TL	391	792	1680	410
12	12	13LBx15	19	TL	391	792	1940	480
16	16	13LBx15	19	TL	391	792	2460	620
33x15.50-16.5	12	12.00	20	TL	394	838	3100	415
14	14	12.00	20	TL	394	838	3390	480
18	18	12.00	20	TL	394	838	3970	620
38x6.5-22.5 (15-22.5)	12	11.75	21	TL	389	1095	4375	480
16	16	11.75	21	TL	389	1095	6900	700
18	18	11.75	21	TL	389	1095	7750	800
10-16.5	10	8.25	19	TL	264	773	2135	520
12	12	8.25	19	TL	264	773	2375	620
12-16.5	10	9.75	19	TL	307	831	2540	450
12	12	9.75	19	TL	307	831	2865	550
14-17.5	14	10.50	20	TL	349	921	3875	550
15-19.5	14	11.75	20	TL	389	1019	4565	480



### SKS4 L-4

- Applications: skid steer, telehandler, aerial boom lift, scissor lift, compact tractor, front backhoe, 3-wheel forklift, rock service
- The block pattern tire specially designed for construction applications
- Ideal for paved surfaces and heavy-duty service
- Excellent cut and chip resistance as well as top rim protection

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg)	Inflation Pressure (kpa)	Max Speed (km/h)
10-16.5	10	8.25	27	TL	264	773	2135	520	10
12-16.5	12	9.75	33	TL	307	831	2865	550	10
14-17.5	14	10.50	37	TL	349	921	3875	550	10
15-19.5	14	11.75	37	TL	389	1019	4565	480	10
12.50-18	12	W9	30	TL	308	965	2650	370	30
14	14	W9	30	TL	308	965	2910	430	30
16.9-24	12	DW15	24	TL	430	1310	3200	250	40
14	14	DW15	24	TL	430	1310	3530	300	40
16.9-28	12	DW15	24	TL	430	1435	3400	250	40
14	14	DW15	24	TL	430	1435	3765	300	40
18.4-26	12	DW16	27	TL	467	1426	3500	250	40
14	14	DW16	27	TL	467	1426	3975	280	40
19.5-24	12	DW16L	27	TL	490	1310	3450	230	40
14	14	DW16L	27	TL	490	1310	3750	280	40
21L-24	14	DW16L	27	TL	540	1385	4125	250	40



### HUL5 L-5

- Applications: skid steer, backhoe loader, telehandler, mining, rock service
- The special tread compound leading to exceptional cut and chip resistance along with excellent wear resistance on all types of terrains
- The extra deep tread with wider and sturdier blocks providing best traction, stability, and puncture resistance

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 30kmh	Inflation Pressure (kpa) 30kmh
10-16.5	10	8.25	27	TL	264	773	2135	520
12-16.5	12	9.75	33	TL	307	831	2865	550
14-17.5	14	10.50	37	TL	349	921	3875	550
15-19.5	14	11.75	37	TL	389	1019	4565	480
18.4-24	14	16.00	37	TL	513	1333	5200	480
18.4-24	14	16.00	37	TL	513	1333	3447(40km/h)	235(40km/h)



### HAL5 L-5

- Applications: skid steer equipment in scrap yards, recycling operations, mining, etc.
- Excellent cut, chip and tear resistance suitable for rough and hard concrete surface
- The deep tread providing an extended tire life-cycle and excellent sidewall protection

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 30kmh	Inflation Pressure (kpa) 30kmh
10-16.5	10	8.25	35	TL	264	773	2135	520
12-16.5	12	9.75	35	TL	307	831	2865	550



### IMPF3 F-3

- Applications: soil tillage operation, implement machinery, trailer
- INDUSTRIAL RIB F3 is an agro-industrial rib-pattern tire designed for field and road transport
- Provides excellent traction on hard soil, asphalt and concrete
- Shock-fortified nylon-cord body resists impacts, cuts and punctures

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 30kmh	Inflation Pressure (kpa) 30kmh
11L-15	10	8LB	13.5	TL	260	810	1190	340
11L-16	10	8LB	13.5	TL	280	835	1240	340
14.5/7.5-16.1	10	11LB	17	TL	375	920	1450	280



### TRENK I-3

- Applications: lawn & garden, trencher equipment, aerial work platform and portable forklift
- Best suited for applications on wet and dry surfaces
- Large contact area to provide best traction and low pressure

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 50kmh	Inflation Pressure (kpa) 50kmh
31x15.50-15	8	13LBx15	22	TL	391	792	1250	310
40(50)-15	10	13LBx15	22	TL	391	792	1450	410
12	12	13LBx15	22	TL	391	792	1650	510



### DFMP L-3

- Applications: telehandler and backhoe loader
- Increased tire life-environmentally friendly
- Protective shoulder rib and low profile vertical sidewall reducing sidewall damage
- Non-directional tread pattern reducing inventory carrying costs
- New tread design reducing ground compaction and surface pressure on hard surfaces

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 30kmh	Inflation Pressure (kpa) 30kmh
370/75-28	14	11.00	34	TL	368 1278	5450	500
	18	11.00	34	TL	368 1278	5950	575
400/75-28	16	12.00	34	TL	399 1328	6500	525
	18	12.00	34	TL	399 1328	7000	600



### SKSR4 R-4

- Applications: compact loader, telehandler
- Heavy-duty sidewall and large curb rib deliver more stability & traction, higher load capacity and greater puncture resistance on the most demanding conditions
- Deep tread, buttressed lugs, full sidewall protection and an aggressive rim deflector to keep out debris

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 40kmh	Inflation Pressure (kpa) 40kmh
445/65-22.5	16	14.00	31	TL	465 1190	4875	550
(18-22.5)	18	14.00	31	TL	465 1190	5345	690
	20	14.00	31	TL	465 1190	6500	750



### SLR4A R-4

- Applications: backhoe loader, telehandler, compact loader, compact dumper
- EXTRA HEAVY CASING-Provides increased durability, larger cut and chip resistance, and extended service life
- SPEPPED REINFORCED LUGS-Provides excellent stability, traction and self-cleaning

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 30kmh	Inflation Pressure (kpa) 30kmh
105/80-18	10	W9	22	TL	274 885	1935	370
	12	W9	22	TL	274 885	2160	430
125/80-18	12	W9	27	TL	308 965	2625	370
	14	W9	27	TL	308 965	2870	430



### SLR4 R-4

- Applications: backhoe loader, telehandler, tractor
- Particularly designed for digging and loading operations as well as municipality and maintenance applications
- EXTRA HEAVY CASING-Provides increased durability, larger cut and chip resistant, and extended service life
- SPEPPED REINFORCED LUGS-Provides excellent stability, traction and self-cleaning

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 40kmh	Inflation Pressure (kpa) 40kmh
14/9-24	12	W13	26	TL	378 1265	2900	290
16/9-24	12	W15L	26	TL	430 1335	3250	260
16/9-28	12	W14L	26	TL	430 1435	3450	260
16/9-30	12	DW15L	27	TL	440 1470	3650	255
18-24	12	W16L	27	TL	487 1374	3750	250
18-26	12	W16L	27	TL	487 1426	3875	250
18-28	12	W16L	27	TL	487 1477	4000	250
18-30	12	DW16L	27	TL	487 1510	4125	250
17.5-24	12	W15L	26	TL	445 1245	3170	260
19.5-24	12	W16L	27	TL	495 1314	3450	230
21L-24	12	DW18A	27	TL	553 1378	3875	220
21L-28	12	W18L	27	TL	550 1530	4000	210



### TIMP R-1

- Applications: tractor, telehandler, backhoe loader, compact loader
- Traction pattern, suitably designed for on and off-the-road use, in all weather conditions particularly suitable for operations on muddy ground
- Patterns design and strong carcass engineered to provide excellent traction to drive wheels, self-cleaning properties and extra cut-chip resistance

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 30kmh	Inflation Pressure (kpa) 30kmh
155/80-24	12	W13	35	TL	394 1240	2900	300
(400/80-24)	14	W13	35	TL	394 1240	3150	350
	16	W13	35	TL	394 1240	3300	400



### INTR1 R-1

- Applications: 2WD-tractor, telehandler, backhoe loader, compact loader
- An agro-industrial tire suitable for field and road transport, municipality/maintenance operations as well as soil tillage applications depending on the tire size
- Traction pattern, suitably designed for on and off-the-road use, in all weather conditions
- Patterns engineered to provide excellent traction to drive wheels and excellent self-cleaning properties

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 30kmh	Inflation Pressure (kpa) 30kmh
100/75-15.3	10	8.00	28	TL	264 760	1525	390
115/80-15	12	8.00	28	TL	290 865	2145	410
115/80-15.3	12	8.00	28	TL	290 865	2145	410
125/80-15.3	14	8.00	28	TL	307 925	2425	410



### INTR4 R-4/1-3

- Applications: 2WD-tractor, telehandler, backhoe loader, compact loader
- An agro-industrial tire suitable for field and road transport, municipality/maintenance operations as well as soil tillage applications depending on the tire size
- Traction pattern, suitably designed for on and off-the-road use, in all weather conditions
- Patterns engineered to provide excellent traction to drive wheels and excellent self-cleaning properties

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 40kmh	Inflation Pressure (kpa) 40kmh
405/70-20	14	13.00	30	TL	410 1075	3750	350
(16/70-20)	16	13.00	30	TL	410 1075	3970	400
405/70-24	14	13.00	30	TL	410 1175	3950	350
(16/70-24)	16	13.00	30	TL	410 1175	4170	400
18-19.5	16	14.00	24	TL	480 1105	4700	600
(445/85D19.5)	18	14.00	24	TL	480 1105	5460	725



### DUMAX568 L-3

- Applications: loader, dozer used in construction stockpile & truck-loading
- Radial design producing good ground grasping and traction in harsh condition, such as construction area, mine sites, quarry, etc.
- Excellent traction and stability, delivering exceptional operator comfort
- Excellent resistance to damage and longer life

Size	Star	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)	
					SW	OD		10km/h	10km/h
15.5R25	★	12.00/1.3	24	TL	395	1275	5800	500	
	★★	12.00/1.3	24	TL	395	1275	7100	650	
17.5R25	★	14.00/1.5	26	TL	420	1487	6500	500	
	★★	14.00/1.5	26	TL	420	1487	8500	650	
20.5R25	★	17.00/2.0	28.5	TL	512	1517	9500	500	
	★★	17.00/2.0	28.5	TL	512	1517	11500	650	
23.5R25	★	19.50/2.5	32	TL	590	1610	12150	500	
	★★	19.50/2.5	32	TL	590	1610	14500	650	
26.5R25	★	22.00/3.0	35	TL	673	1750	15000	500	
	★★	22.00/3.0	35	TL	673	1750	18500	650	



### W-1 E-3/L-3

- Applications: loader, dozer, earthmover, grader, scraper operating under the relatively severe conditions
- The tread compound providing cut-and-chip-resistant properties and suites best for loading and dozing operations
- Aggressive, durable lug design, non-directional tread design and wide base construction, which can provide high flotation, excellent traction, improved stability and reduced ground pressure
- The specially-formulated synthetic rubber compound can offer excellent cutting and heat resistance and help to prevent sidewall cracking

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)	
					SW	OD		10km/h	50km/h
13.00-24	12	10.00	24	TT/TL	350	1350	5600*3000	450*300	
	16	10.00	25.5	TT/TL	375	1370	7300*4000	550*375	
14.00-24	20	10.00	25.5	TT/TL	375	1370	8500*4625	700*475	
	24	10.00	25.5	TT/TL	375	1370	9500*5150	850*575	
	28	10.00	25.5	TT/TL	375	1370	10000*5600	925*650	
	32	10.00	25.5	TT/TL	375	1370	10900*6150	1050*750	
14.00-25	16	10.00/1.5	25.5	TT/TL	375	1370	7300*4000	550*375	
	20	10.00/1.5	25.5	TT/TL	375	1370	8500*4625	700*475	
	24	10.00/1.5	25.5	TT/TL	375	1370	9500*5150	850*575	
	28	10.00/1.5	25.5	TT/TL	375	1370	10000*5600	925*650	
16.00-24	12	10.00/1.5	25.5	TT/TL	375	1370	7300*4000	550*375	
	16	10.00/1.5	25.5	TT/TL	375	1370	8500*4625	700*475	
	20	10.00/1.5	25.5	TT/TL	375	1370	9500*5150	850*575	
	24	10.00/1.5	25.5	TT/TL	375	1370	10000*5600	925*650	
16.00-24	28	10.00/1.5	25.5	TT/TL	375	1370	10900*6150	1050*750	
	32	10.00/1.5	25.5	TT/TL	375	1370	11500*6700	1125*825	
	36	10.00/1.5	25.5	TT/TL	375	1370	12150*7250	1175*875	
	40	10.00/1.5	25.5	TT/TL	375	1370	12800*7800	1225*925	
16.00-24	24	11.25/2.0	28.5	TT/TL	430	1495	10600*8000	850*475	
	28	11.25/2.0	28.5	TT/TL	430	1495	11500*8700	750*575	
	32	11.25/2.0	28.5	TT/TL	430	1495	12500*9300	875*650	
	36	11.25/2.0	28.5	TT/TL	430	1495	13500*9900	950*725	
16.00-25	12	11.25/2.0	28.5	TT/TL	430	1495	10600*8000	850*475	
	16	11.25/2.0	28.5	TT/TL	430	1495	11500*8700	750*575	
	20	11.25/2.0	28.5	TT/TL	430	1495	12500*9300	875*650	
	24	11.25/2.0	28.5	TT/TL	430	1495	13500*9900	950*725	
18.00-24	12	13.00/2.5	31.5	TT/TL	500	1615	12500*7300	550*425	
	16	13.00/2.5	31.5	TT/TL	500	1615	13600*8000	650*500	
	20	13.00/2.5	31.5	TT/TL	500	1615	15000*8750	750*575	
	24	13.00/2.5	31.5	TT/TL	500	1615	16000*9250	850*625	
18.00-25	16	13.00/2.5	31.5	TT/TL	500	1615	17000*9700	950*700	
	20	13.00/2.5	31.5	TT/TL	500	1615	12500*7300	550*425	
	24	13.00/2.5	31.5	TT/TL	500	1615	13600*8000	650*500	
	28	13.00/2.5	31.5	TT/TL	500	1615	15000*8750	750*575	
17.5-25	16	14.00/1.5	25.5	TT/TL	445	1350	7300*4250	475*300	
	20	14.00/1.5	25.5	TT/TL	445	1350	8250*5000	575*350	
	24	14.00/1.5	25.5	TT/TL	445	1350	9250*5600	700*475	
	28	14.00/1.5	25.5	TT/TL	445	1350	10000*6000	750*500	
20.5-25	16	17.00/2.0	30	TT/TL	520	1490	8250*5450	350*275	
	20	17.00/2.0	30	TT/TL	520	1490	9500*6000	450*325	
	24	17.00/2.0	30	TT/TL	520	1490	10300*6700	525*400	
	28	17.00/2.0	30	TT/TL	520	1490	11000*7200	575*425	
23.5-25	16	19.50/2.5	31.5	TT/TL	595	1615	9500*6150	300*225	
	20	19.50/2.5	31.5	TT/TL	595	1615	10900*7300	375*300	
	24	19.50/2.5	31.5	TT/TL	595	1615	12500*8000	475*350	
	28	19.50/2.5	31.5	TT/TL	595	1615	13600*8750	550*400	
26.5-25	16	22.00/3.0	35	TT/TL	675	1750	14000*9250	400*300	
	20	22.00/3.0	35	TT/TL	675	1750	15500*10000	475*350	
	24	22.00/3.0	35	TT/TL	675	1750	17000*11000	550*425	
	28	22.00/3.0	35	TT/TL	675	1750	18500*12000	625*475	
29.5-25	16	25.00/3.5	38	TL	750	1875	17500*11500	425*325	
	20	25.00/3.5	38	TL	750	1875	20000*12950	525*400	
	24	25.00/3.5	38	TL	750	1875	21200*14000	575*425	
	28	25.00/3.5	38	TL	750	1875	22500*15000	625*450	
16/70-20	14	13.00	23	TT/TL	410	1075	5150*2900	430*350	
	14	13.00	25	TT/TL	410	1175	5600*3350	450*350	



### W-2 E-3/L-3

- Applications: loader, dozer, earthmover, grader, scraper operating under the relatively severe conditions
- BLOCK PATTERN TYRE SERIES suitable to be operated under many conditions
- Aggressive, durable lug design, non-directional tread design and wide base construction, can provide high flotation, excellent traction, improved stability and reduced ground pressure
- The specially-formulated synthetic rubber compound can offer excellent cutting and heat resistance and help to prevent sidewall cracking

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)	
					SW	OD		10km/h	50km/h
1600-24	24	11.25/2.0	28.5	TT/TL	430	1495	10600*8000	850*475	
	28	11.25/2.0	28.5	TT/TL	430	1495	11500*8700	750*575	
	32	11.25/2.0	28.5	TT/TL	430	1495	12500*9300	875*650	
1600-25	24	11.25/2.0	28.5	TT/TL	430	1495	10600*8000	850*475	
	28	11.25/2.0	28.5	TT/TL	430	1495	11500*8700	750*575	
	32	11.25/2.0	28.5	TT/TL	430	1495	12500*9300	875*650	
1800-24	24	13.00/2.5	31.5	TT/TL	500	1615	12500*7300	550*425	
	28	13.00/2.5	31.5	TT/TL	500	1615	13600*8000	650*500	
	32	13.00/2.5	31.5	TT/TL	500	1615	15000*8750	750*575	
	36	13.00/2.5	31.5	TT/TL	500	1615	16000*9250	850*625	
1800-25	24	13.00/2.5	31.5	TT/TL	500	1615	17000*9700	950*700	
	28	13.00/2.5	31.5	TT/TL	500	1615	12500*7300	550*425	
	32	13.00/2.5	31.5	TT/TL	500	1615	13600*8000	650*500	
	36	13.00/2.5	31.5	TT/TL	500	1615	15000*8750	750*575	
155-25	12	12.00/1.3	24	TT/TL	395	1275	5600*3250	400*250	
	16	12.00/1.3	24	TT/TL	395	1275	6500*3750	525*325	
	16	14.00/1.5	24	TT/TL	445	1350	7300*4250	475*300	
	20	14.00/1.5	24	TT/TL	445	1350	8250*5000	575*350	
205-25	16	17.00/2.0	29	TT/TL	520	1490	8250*5450	350*275	
	20	17.00/2.0	29	TT/TL	520	1490	9500*6000	450*325	
	24	17.00/2.0	29	TT/TL	520	1490	10300*6700	525*400	
235-25	16	19.50/2.5	30	TT/TL	595	1615	9500*6150	300*225	
	20	19.50/2.5	30	TT/TL	595	1615	10900*7300	375*300	
	24	19.50/2.5	30	TT/TL	595	1615	12500*8000	475*350	
	28	19.50/2.5	30	TT/TL	595	1615	13600*8750	550*400	
265-25	24	22.00/3.0	32	TT/TL	675	1750	14000*9250	400*300	
	28	22.00/3.0	32	TT/TL	675	1750	15500*10000	475*350	
	32	22.00/3.0	32	TT/TL	675	1750	17000*11000	550*425	
295-25	28	25.00/3.5	32	TL	750	1875	17500*11500	425*325	
	34	25.00/3.5	36	TL	750	1875	20000*12950	525*400	
295-29	28	25.00/3.5	38	TL	750	1875	19000*12150	425*325	
	34	25.00/3.5	38	TL	750	1875	21200*14000	525*400	

### W-3A E-2

- Applications: excavators in road construction works, soft and muddy ground
- Special tread compound producing particular resistance to cuts and snags, extremely strong traction, good self-cleaning
- Wide tread pattern providing good floating and excellent driving properties
- The strong casing providing extraordinary resistance to impacts and shocks even in heavy-duty operations



Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)	
					SW	OD		10km/h	50km/h
9.00-20	14	7.00	22	TT	262	1024	4365*2770	760*720	
	16	7.00	22	TT	262	1024	4745*3000	830*780	
	18	7.00	22	TT	262	1024	5105*3230	910*870	
10.00-20	16	7.							


**W-3C E-3**

- Applications: heavy duty excavator and forklift in road construction works, soft and muddy ground, and highway crane on road and port
- Special tread compound producing particular resistance to cuts and snags, extremely strong traction, good self-cleaning
- Wide tread pattern providing good floating and excellent driving properties
- The strong casing providing extraordinary resistance to impacts and shocks even in heavy-duty operations

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 70km/h	Inflation Pressure (kpa) 70km/h
12.00-24	20	8.50	22	TT	316	1130	3750	550
	24	8.50	22	TT	316	1130	4350	600


**W-3D G-2**

- Applications: scraper and motor grader in city and country maintenance work, construction and mine applications
- Pattern design producing excellent traction and self-cleaning features
- A special compound enabling an extended tire life-cycle and heavy-duty service

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 10km/h/40km/h	Inflation Pressure (kpa) 10km/h/40km/h
13.00-24	12	8.00	25	TT/TL	335	1275	5600*2725	450*300
	16	8.00	25	TT/TL	335	1275	8500*3275	600*425
14.00-24	12	8.00	25	TT/TL	360	1345	6300*3075	425*275
	16	8.00	25	TT/TL	360	1345	7300*3650	550*375
16.00-24	16	10.00VA	28.5	TT/TL	425	1460	8250*4500	425*325


**W-3DN G-2**

- Applications: scraper and motor grader in city and country maintenance work, construction and mine applications
- Pattern design producing excellent traction and self-cleaning features
- A special compound enabling an extended tire life-cycle and heavy-duty service

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 10km/h/40km/h	Inflation Pressure (kpa) 10km/h/40km/h
13.00-24	12	8.00	28	TT/TL	366	1298	5600*2725	450*300
	16	8.00	28	TT/TL	366	1298	6500*3275	600*425
14.00-24	12	8.00	28	TT/TL	398	1370	6300*3075	425*275
	16	8.00	28	TT/TL	398	1370	7300*3650	550*375


**W-3E G-2**

- Applications: scraper and motor grader in city and country maintenance work, construction and mine applications
- Precision-angled bars maximizing traction in soft soil and providing long wear
- Open shoulder grooves providing self-cleaning, excellent traction and less slipping
- Tough and durable casing producing the most widely retreaded tire in the industry

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 40km/h	Inflation Pressure (kpa) 40km/h
15.5-25	12	12.00/1.3	23.5	TT/TL	395	1275	2650	225
	16	12.00/1.3	23.5	TT/TL	395	1275	3200	325
17.5-25	12	14.00/1.5	23	TT/TL	445	1350	2900	200
	16	14.00/1.5	23	TT/TL	445	1350	3350	275
20.5-25	12	17.00/2.0	26.5	TT/TL	520	1490	3550	175
	16	17.00/2.0	26.5	TT/TL	520	1490	4000	225
23.5-25	12	19.00/2.5	30.5	TT/TL	595	1615	4750	200
	16	19.00/2.5	30.5	TT/TL	595	1615	5450	250


**W-3EN G-2**

- Applications: scraper and motor grader in city and county maintenance work, construction and mine applications
- The strong, larger and durable casing designed to extend life service and maximize equipment capacities
- Pattern design producing excellent traction and self-cleaning features

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 40km/h	Inflation Pressure (kpa) 40km/h
17.5-25	12	14.00/1.5	26	TT/TL	464	1366	2900	200
	16	14.00/1.5	26	TT/TL	464	1366	3350	275
	20	14.00/1.5	26	TT/TL	464	1366	3650	325


**W-4 E-4**

- Applications: Empty Container Handler, Reach Stacker, Straddle & Shuttle Carrier, Rubber Tyre Gantry (RTG), Automated Guide Vehicles (AGV), Harbour Mobile Crane (HMC)
- Special compound and design suitable for handling equipment operating in airport, yard, port and so on
- Deep tread pattern and wide riding area providing good cutting and wear resistances, improving ride properties on gravel road

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 10km/h/30km/h	Inflation Pressure (kpa) 10km/h/30km/h
12.00-24	24	8.50	35	TT/TL	335	1272	7600*3250	975*650
	28	10.00W	44.5	TT/TL	404	1412	10000*5600	925*650
14.00-24	24	10.00	44.5	TT/TL	408	1412	9500*5150	850*675
	28	10.00	44.5	TT/TL	408	1412	10000*5600	925*650
16.00-25	28	11.25/2.0	50	TT/TL	430	1495	11500*6700	750*775
	32	11.25/2.0	50	TT/TL	430	1495	12500*7300	875*650
	36	11.25/2.0	50	TT/TL	430	1495	13600*7750	975*725
	40	11.25/2.0	50	TT/TL	430	1495	14500*8150	1075*775
18.00-25	28	13.00/2.5	54	TL	500	1615	13600*8000	650*500
	32	13.00/2.5	54	TL	500	1615	15000*8750	750*575
	36	13.00/2.5	54	TL	500	1615	16000*9250	850*625
	40	13.00/2.5	54	TL	500	1615	17000*9750	950*700
21.00-25	28	15.00	57	TL	570	1800	19000*10250	1100*900
	32	15.00	57	TL	570	1800	16500*9500	575*425
	36	15.00	57	TL	570	1800	17500*10300	650*500
	40	15.00	57	TL	570	1800	19500*10900	750*550
24.00-29	30	17.00	54	TL	655	1975	20800*11800	805*625
	38	17.00	54	TL	655	1975	21800*12500	525*475
	42	17.00	54	TL	655	1975	24600*14000	825*475
	48	17.00	54	TL	655	1975	27400*15900	725*500
18.00-33	32	13.00/2.5	53.5	TL	500	1820	30200*16400	825*625
	36	13.00/2.5	53.5	TL	500	1820	17500*10000	750*575
	42	13.00/2.5	53.5	TL	500	1820	18500*10600	825*625
	44	13.00/2.5	53.5	TL	500	1820	20000*11500	975*725


**W-4A E-4**

- Applications: scraper & heavy dump truck operation on relatively tough road surface in areas like mining areas, tunnel, quarry construction site, etc.
- Deep tread pattern and wide riding area providing good cutting and wear resistances, improving ride properties on gravel road
- Special compound and design extending the tire service life

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 10km/h/30km/h	Inflation Pressure (kpa) 10km/h/30km/h
18.00-33	32	13.00/2.5	53.5	TL	500	1820	17500*10000	750*575
	36	13.00/2.5	53.5	TL	500	1820	18500*10600	825*625
	42	13.00/2.5	53.5	TL	500	1820	20000*11500	975*725
16.00-25	28	11.25/2.0	50	TL	430	1495	11500*6700	750*575
	32	11.25/2.0	50	TL	430	1495	12500*7300	875*650
	36	11.25/2.0	50	TL	430	1495	13600*7750	975*725
	40	11.25/2.0	50	TL	430	1495	14500*8150	1075*775
18.00-25	28	13.00/2.5	54	TL	500	1615	13600*8000	650*500
	32	13.00/2.5	54	TL	500	1615	15000*8750	750*575
	36	13.00/2.5	54	TL	500	1615	16000*9250	850*625
	40	13.00/2.5	54	TL	500	1615	17000*9750	950*700
21.00-25	28	15.00	57	TL	570	1800	19000*10250	1100*900
	32	15.00	57	TL	570	1800	16500*9500	575*425
	36	15.00	57	TL	570	1800	17500*10300	650*500
	40	15.00	57	TL	570	1800	19500*10900	750*550
21.00-33	42	15.00	57	TL	570	1800	20800*11800	805*625
	44	15.00	57	TL	570	1800	22400*12400	775*625
21.00-35	36	15.00/3.0	54	TL	570	1800	32500*14200	875*725
	40	15.00/3.0	54	TL	570	2005	23000*12650	750*650
24.00-35	44	15.00/3.0	54	TL	570	2005	24300*14000	825*625
	42	15.00/3.0	57	TL	653	2130	25000*14500	900*675
	42	15.00/3.0	57	TL	653	2130	29000*16500	750*550
	48	15.00/3.0	57	TL	653	2130	31500*18500	850*650



### W-4B E-4

- Applications: port, underground mining, Straddle & Shuttle Carrier, RTG Reach Stacker, Empty Container Handler, AGV, HMC, LHD
- Deep tread, the extra thick sidewall and the tough casing providing exceptional durability minimizing the risk of punctures and accidental damages
- Excellent cut and chip resistance, which is particularly suitable for rough and hard surfaces
- Specially designed rim guard ensuring protection against flats and wheel damage in the rim flange area
- Deeper tread making the longer service life than W-4

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 10km/h/30km/h	Inflation Pressure (kpa) 10km/h/30km/h
12.00-24	24	8.50	55	TT/TL	335 1272	8900*3250	825*650
14.00-24	28	10.00W	65	TT/TL	404 1412	10000*5600	925*650
18.00-25	28	13.00/2.5	75	TL	500 1815	13600*8000	650*500
	32	13.00/2.5	75	TL	500 1815	15000*8750	750*575
	36	13.00/2.5	75	TL	500 1815	16000*9250	850*625
	40	13.00/2.5	75	TL	500 1815	17000*9750	950*700
	48	13.00/2.5	75	TL	500 1815	19000*10250	1100*900



### W-5 E-3

- Applications: heavy-duty scraper and loader operating on mining areas, tunnel, quarry, construction site, etc.
- Center riding rib providing a smooth ride and improving lateral stability
- Deep, non-directional, rock service tread designed for the challenges of large equipment demands, such as long-time service, self-cleaning, cut resistance, etc.

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 10km/h/30km/h	Inflation Pressure (kpa) 10km/h/30km/h
33.5-33	32	28.00/4.0	43	TL	850 2240	25750*18500	425*325
	38	28.00/4.0	43	TL	850 2240	29000*18500	525*400
	44	28.00/4.0	43	TL	850 2240	32300*18800	625*475
33.25-35	32	27.00/3.5	43	TL	845 2240	25750*18000	450*325
	38	27.00/3.5	43	TL	845 2240	28000*18000	550*400
	44	27.00/3.5	43	TL	845 2240	32300*18800	625*475
37.25-35	36	31.00/4.0	43	TL	945 2380	30750*19500	450*325
	42	31.00/4.0	43	TL	945 2380	33500*21800	525*400
37.5-33	36	32.00/4.5	43	TL	950 2390	31500*20000	450*325
	42	32.00/4.5	43	TL	950 2390	34500*22400	525*400
33.25-29	26	27.00/3.5	38	TL	845 2080	20800*13600	350*275
	32	27.00/3.5	38	TL	845 2080	23600*15000	450*325



### W-5A L-4

- Applications: giant loader in the ore and coal mine sites
- Extra deep tread producing excellent rock type damage resistance and long tread life
- Open non-directional tread pattern providing all round traction with excellent self-cleaning
- Cut Resistant Breaker (CRB) construction providing increased strength and durability without sacrificing heat resistance

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 25km/h/50km/h	Inflation Pressure (kpa) 25km/h/50km/h
4565-45	58	36.00/4.5	116	TL	1015 2350	50000 (10km/h)	675 (10km/h)
5090-57	68	36.00/6.0	97	TL	1280 3540	102800*90000	650*650
5280-57	72	36.00/6.0	97	TL	1320 3550	116300*102000	650*650
5560-57	72	44.00/6.0	100	TL	1400 3560	120000*100000	650*650
55.9/60-57	76	44.00/6.0	100	TL	1400 3720	137800*117800	750*750
53.5/65-57	76	44.00/6.0	100	TL	1350 3920	129200*115600	750*750
6565-57	82	52.00/6.0	100	TL	1650 3730	121300*105000	600*800



### W-5B L-4

- Applications: giant loader in the ore and coal mine sites
- Extra deep tread producing excellent rock type damage resistance and long tread life
- Open non-directional tread pattern providing all round traction with excellent self-cleaning
- Cut Resistant Breaker (CRB) construction providing increased strength and durability without sacrificing heat resistance

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 25km/h/50km/h	Inflation Pressure (kpa) 25km/h/50km/h
5885-57	84	47.00/6.0	100	TL	1450 3928	142800*125000	780*780
7070-57	84	60.00/6.0	100	TL	1750 3928	199800*173000	800*800



### W-5C L-4

- Applications: loader and dozer in quarry and harsh pavement
- Non-directional design for heavy duty rock service
- Ideal tire for severe operations requiring added cut resistance, sidewall protection and exceptional traction, excellent tread cleaning design

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 10km/h	Inflation Pressure (kpa) 10km/h
17.5-25	16	14.00/1.5	46	TL	445 1400	7300	475



### W-6 L-5

- Applications: loader & earthmover used in the harsh conditions, such as construction and mining areas
- Extra deep tread and strong casing design providing excellent rock type damage resistance and long tread life in heavy duty
- Open non-directional tread pattern producing all round traction with excellent self-cleaning

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 10km/h	Inflation Pressure (kpa) 10km/h
17.5-25	20	14.00/1.5	62	TL	445 1350	8250	575
	24	14.00/1.5	62	TL	445 1350	9250	700
20.5-25	20	17.00/2.0	69	TL	520 1490	9500	450
	24	17.00/2.0	69	TL	520 1490	10300	525
23.5-25	20	19.50/2.5	76	TL	595 1615	10900	375
	24	19.50/2.5	76	TL	595 1615	12500	475
	28	19.50/2.5	76	TL	595 1615	19800	550
26.5-25	24	22.00/3.0	87	TL	675 1750	14000	400
	28	22.00/3.0	87	TL	675 1750	15500	475
	32	22.00/3.0	87	TL	675 1750	17000	550
29.5-25	28	25.00/3.5	92	TL	750 1875	17500	425
	34	25.00/3.5	92	TL	750 1875	20000	525
29.5-28	28	25.00/3.5	92	TL	750 1975	19000	425
	34	25.00/3.5	92	TL	750 1975	21200	525
3565-33	30	28.00/3.5	97	TL	890 2030	21200	425
	36	28.00/3.5	97	TL	890 2030	23600	525
	42	28.00/3.5	97	TL	890 2030	26500	625
4565-39	36	32.00/4.0	116	TL	1140 2410	34500	400
	46	32.00/4.0	116	TL	1140 2410	41250	525
	4565-45	38	36.00/4.5	116	TL	1015 2350	38750
4565-46	46	36.00/4.5	116	TL	1015 2350	43750	525
	58	36.00/4.5	116	TL	1015 2350	50000	675



### W-6A L-5

- Applications: giant loader in the ore and coal mine sites
- Extra deep tread producing excellent rock type damage resistance and long tread life
- Open non-directional tread pattern providing all round traction with excellent self-cleaning
- Cut Resistant Breaker (CRB) construction providing increased strength and durability without sacrificing heat resistance

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 10km/h	Inflation Pressure (kpa) 10km/h
5065-51	62	40.00/4.5	127	TL	1270 2995	63000	650
67.5/60-51	64	46.00/5.5	137	TL	1680 3520	107300	680



### W-6B L-4

- Applications: loader & earthmover used in the harsh conditions, such as construction and mining areas
- Extra deep tread and strong casing design providing excellent rock type damage resistance and long tread life in heavy duty
- Open non-directional tread pattern producing all round traction with excellent self-cleaning

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 10km/h	Inflation Pressure (kpa) 10km/h
23.5-25	20	19.50/2.5	54	TL	585 1615	10900	375
	24	19.50/2.5	54	TL	585 1615	12500	475
	28	19.50/2.5	54	TL	585 1615	19800	550
26.5-25	24	22.00/3.0	54	TL	675 1750	14000	400
	28	22.00/3.0	54	TL	675 1750	15500	475
	32	22.00/3.0	54	TL	675 1750	17000	550



### W-7 L-5S

- Applications: LHD, underground mining loader, shuttle car in rocky harsh conditions of pit lane, tunnel, underground mines
- Extra deep tread depth provides long tread life in extreme conditions
- Smooth tread design provides the maximum rock type damage resistance
- Features Aralon Cut Resistant Breaker (CRB) construction, which provides increased strength and durability without sacrificing heat resistance

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)	
					SW	OD		10kmh	10kmh
10.00-20	14	8.00	30.5	TT/TL	279	1068	4250	850	
	16	8.00	30.5	TT/TL	279	1068	4600	750	
12.00-20	16	8.50	56	TT/TL	315	1145	5450	700	
	20	8.50	56	TT/TL	315	1145	6350	875	
12.00-24	20	8.50V	56	TT/TL	315	1245	6900	825	
	24	8.50V	56	TT/TL	315	1245	7500	975	
14.00-24	20	10.00W	63.5	TT/TL	375	1370	8500	700	
	24	10.00W	63.5	TT/TL	375	1370	9500	850	
	28	10.00W	63.5	TT/TL	375	1370	10000	925	
	32	10.00W	63.5	TT/TL	375	1370	10900	1050	
	36	10.00W	63.5	TT/TL	375	1370	11400	1100	
	16.00-25	28	11.25/2.0	71	TL	430	1395	11500	750
32	11.25/2.0	71	TL	430	1395	12500	875		
	36	11.25/2.0	71	TL	430	1395	13600	975	
	40	11.25/2.0	71	TL	430	1395	14500	1075	
17.5-25	20	14.00/1.5	62	TL	445	1350	8200	800	
	24	14.00/1.5	62	TL	445	1350	8950	850	
18.00-25	32	13.00/2.5	78.5	TL	523	1866	15000	750	
	36	13.00/2.5	78.5	TL	523	1866	16000	850	
	40	13.00/2.5	78.5	TL	523	1866	17000	950	
	50	13.00/2.5	78.5	TL	523	1866	19500	1200	
	20.5-25	20	17.00/2.0	69	TL	520	1490	9500	450
24	17.00/2.0	69	TL	520	1490	10300	525		
	20	19.50/2.5	76	TL	595	1615	10900	375	
24	19.50/2.5	76	TL	595	1615	12500	475		
	28	19.50/2.5	76	TL	595	1615	13600	550	
26.5-25	36	22.00/3.0	87.5	TL	695	1750	18500	625	
	40	22.00/3.0	87.5	TL	695	1750	19800	750	
	50	22.00/3.0	87.5	TL	695	1750	23500	900	
29.5-25	36	25.00/3.5	95	TL	750	1875	21200	550	
	40	25.00/3.5	95	TL	750	1875	22500	625	
	50	25.00/3.5	95	TL	750	1875	26700	775	
29.5-29	36	25.00/3.5	95	TL	750	1975	22000	550	
	40	25.00/3.5	95	TL	750	1975	23600	625	
	50	25.00/3.5	95	TL	750	1975	26800	775	
39/65-33	42	29.00/3.5	97	TL	890	2030	26500	625	
	48	29.00/3.5	97	TL	890	2030	29000	725	
45/65-45	58	36.00/4.5	116	TL	1015	2350	50000	875	



### W-7A C-1

- Applications: compactor and roller tractor
- Higher stability, wider contact area, and smooth profile for efficient compaction
- Special compound providing high heat resistance and longer tire life
- Low rolling resistance for economy performance

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)	
					SW	OD		10kmh	10kmh
7.50-15	14	6.00	15	TT	215	780	2950	825	
9.00-20	16	7.00	15	TT	259	1018	4750	725	
10.00-20	16	7.50	16	TT	278	1055	5300	800	
11.00-20	18	8.00	16	TT	293	1085	6000	825	
12.00-20	20	8.50	18	TT	315	1125	6750	900	



### W-8 E-7/C-1

- Variable compounds for different pattern and different applications
- E-7 used in the sandy and desert areas, C-1 for compactor in road construction
- E-7 special compound producing good resistance to the high temperature
- Flat and wide foot print suitable for flotation applications on soft soil, orchards, etc.
- Tread specially designed to give minimum ground disturbance
- Increased tread depth and strong carcass ensuring long life

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)	
					SW	OD		16kmh/30kmh	10kmh/30kmh
16.00-20	16	10.00W	15	TT/TL	420	1370	5650*3150	240*170	
23.1-26	12	DW20.00	28	TT/TL	587	1580	5150*3650	240*170	
	14	DW20.00	28	TT/TL	587	1580	5710*4050	275*200	
24-21	18	DW20.00	28	TT/TL	587	1580	6080*4300	350*230	
	18	18.00/1.5	13	TT/TL	610	1370	5800*3875	240*170	
24.00-20.5	16	18.00/0.5	13	TT/TL	610	1370	5800*3875	240*170	



### W-9

- Applications: forklift vehicles operating in port, airport, factory and warehouse sites, etc.
- Special compound producing good cutting, wear resistances, long lift service
- Wide and thick tread design providing good ground contact, traction and self-cleaning

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)	
					SW	OD		25kmh Drive/Steer	25kmh Drive/Steer
8.25-15	12	6.50	20	TT	235	840	3480*2945	720	
	14	6.50	20	TT	235	840	3775*3185	830	
	16	6.50	20	TT	235	840	4050*3550	925	



### W-9A

- Applications: forklift vehicles operating in port, airport, factory and warehouse sites, etc.
- Special compound producing good cutting, wear resistances, long lift service
- Wide and thick tread design providing good ground contact, traction and self-cleaning

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)	
					SW	OD		25kmh Drive/Steer	25kmh Drive/Steer
7.00-9	10	5.00S	11	TT	190	590	1995/1685	860	
8.25-12	12	7.00	15	TT	235	765	3060/2585	720	



### W-9B

- Applications: forklift vehicles operating in port, airport, factory and warehouse sites, etc.
- Special compound producing good cutting, wear resistances, long lift service
- Wide and thick tread design providing good ground contact, traction and self-cleaning

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)	
					SW	OD		25kmh Drive/Steer	25kmh Drive/Steer
5.00-8	8	3.50D	10	TT	137	470	1000*845	790	
9.00-20	10	3.50D	10	TT	137	470	1150*970	1000	
	14	4.33R	10	TT	173	485	1505*1270	970	
10.00-20	16	4.33R	10	TT	173	485	1895*1450	1000	
6.00-9	10	4.00E	10	TT	160	540	1505*1270	860	
6.50-10	10	5.00F	11	TT	175	590	1855*1400	790	
7.00-12	12	5.00S	14	TT	190	676	2375*2005	860	
8.25-12	12	7.00	15	TT	235	765	3060*2585	720	
7.00-15	12	5.50F	15	TT	200	750	2870*2420	860	
7.50-15	12	6.00	16	TT	215	780	3075*2680	790	
7.50-16	12	6.00G	18	TT	215	805	3195*2700	790	
	14	6.00G	18	TT	215	805	3535*2925	925	
	16	6.00G	18	TT	215	805	3875*3280	1000	
8.15-15	12	7.00	17	TT	215	704	2790*2355	830	
	14	7.00	17	TT	215	704	3050*2575	870	
8.00-20	18	7.00	22	TT	259	789	4895*2970	860	
10.00-20	18	7.50	23	TT	280	1055	5195*3865	860	
(24065-20)	20	7.50	23	TT	280	1055	6275*4815	930	
	24	7.50	23	TT	280	1055	7385*5670	1025	
12.00-20	20	8.50	24	TT	315	1125	6835*4200	860	
	24	8.50	24	TT	315	1125	7650*4780	930	
(33065-20)	28	8.50	24	TT	315	1125	8510*5480	1025	
	16	7.50	20	TT	250	735	4365*3360	825	
(25070-15)	18	7.50	20	TT	250	735	4745*3650	860	
	20	7.50	20	TT	250	735	5135*3950	1075	
3.00-15	18	8.00	22	TT	300	840	5850*4500	850	
	(31570-15)	20	8.00	22	TT	300	840	6500*5000	800




**W-10 LS-1/HF-2**

- Applications: agricultural and forestry tractor, harvester, petroleum exploration vehicle (vibrator machine) and fuel truck
- Deeper-tread flotation tires for maximum traction in the toughest conditions
- Special wide-arc design protecting sidewall from cuts and snags
- 23-degree angle bar for good contact and excellent traction

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 40km/h	Inflation Pressure (kPa) 40km/h
54/37 00-25	12	32.00	37	TL	935 1430	5890	240
	20	32.00	37	TL	935 1430	7660	380
66/43 00-25	16	36.00	37	TL	1050 1700	6100	290
	20	36.00	37	TL	1050 1700	6600	310


**W-10A HF-1**

- Applications: monster performance car
- Low ply rating and low tread depth design lightening tires
- Super wide tread design and special construction improving the tire stability and casing strength

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 50km/h	Inflation Pressure (kPa) 50km/h
66/43 00-25	10	36.00	13	TL	1050 1650	4500	170
	12	36.00	13	TL	1050 1650	5000	210


**W-10B E-7/HF-1**

- Applications: petroleum exploration vehicle (vibrator machine) and fuel truck
- Low-sectional tire with super base providing
  1. High traction performance on soft road surface
  2. Extreme stability
  3. Low tire press on ground lightly without sinking
  4. Promotion of the efficiency of off-the-road vehicles

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 40km/h	Inflation Pressure (kPa) 40km/h
66/44 00-25	16	36.00	12	TL	1075 1720	6150	280
	20	36.00	12	TL	1075 1720	7000	340


**W-11 E-7**

- Applications: off-road vehicles on sandy and desert areas, and paver and compactor machines
- Special compound producing the resistance to extreme high temperature
- Wide tread, round shoulder and streamlined pattern design providing stable ride, good floating force, excellent steering ability and uniform tread wear

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 10km/h/50km/h	Inflation Pressure (kPa) 10km/h/50km/h
825-16	8	6.00	11	TT/TL	240 850	1500*980	250
900-16	8	6.50H	11	TT/TL	245 890	1700*975	245
2100-25	16	15.00/3.0	16	TL	570 1685	10000*5800	245
	32	15.00/3.0	16	TL	570 1685	15450*9150	450


**W-12 E-7**

- Applications: off-road vehicles, loaders and oil detection platform operating on sandy and desert areas, and paver and compactor machines
- Special compound producing the resistance to extreme high temperature
- Wide tread, round shoulder and streamlined pattern design providing stable ride, good floating force, excellent steering ability and uniform tread wear

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 10km/h/50km/h	Inflation Pressure (kPa) 10km/h/50km/h
1400-20	18	7.50V	9	TT/TL	375 1220	4125*2360	245
1600-20	16	10.00VV	15	TT/TL	419 1323	5450*3150	245
2400-20.5	16	18.00/0.5	14	TT/TL	610 1370	5600*3875	240
24-21	16	18.00/1.5	16	TT/TL	610 1370	5600*3875	240
1800-25	18	10.00/1.5	16	TL	470 1557	7750*4375	245
285-25	28	25.00/3.5	21	TL	750 1830	12835*10000	240
3600-51	42	26.00/5.0	26	TL	990 3075	48000*26500	240
	50	26.00/5.0	26	TL	990 3075	55000*29870	280
	58	26.00/5.0	26	TL	990 3075	61000*33250	350


**W-12A E-7**

- Applications: off-road vehicles operating on sandy and desert areas
- Special compound producing the resistance to extreme high temperature
- Wide tread, round shoulder and streamlined pattern design providing stable ride, good floating force, excellent steering ability and uniform tread wear

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 10km/h/50km/h	Inflation Pressure (kPa) 10km/h/50km/h
1400-20	18	7.50V	9	TT/TL	375 1220	4125*2360	245


**W-15 E-3**

- Applications: mining truck and fuel truck
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 70km/h	Inflation Pressure (kPa) 70km/h
1100-20	18	8.00	22	TT	293 1085	3835	910
1200-20	18	8.50	22	TT	315 1125	3940	810
	20	8.50	22	TT	315 1125	4200	880


**W-15A E-3**

- Applications: mining truck and fuel truck
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW OD	Max Load (kg) 70km/h	Inflation Pressure (kPa) 70km/h
1400-20	20	10.00	20	TT	375 1265	5250	770
	28	10.00	20	TT	375 1265	5860	900
1400-25	28	10.00VV	25.5	TT	375 1370	5600	650
	30	10.00VV	25.5	TT	357 1318	6150	750



### W-15B E-3

- Applications: mining truck and fuel truck
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 70km/h	Inflation Pressure (kpa) 70km/h
11.00-20	18	8.50	22	TT	293	1085	3835	910



### W-15C E-3

- Applications: mining truck and fuel truck
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 70km/h	Inflation Pressure (kpa) 70km/h
13.00-25	30	8.5/1.3	22	TT	350	1300	5125	750
	32	8.5/1.3	22	TT	350	1300	5375	800



### W-16 E-2

- Applications: military vehicles, such as tank, armored car, and cross-country truck
- All-terrain tire applied on highway and generally paved road
- The unique pattern design and special compound design producing the overload, high-speed, and abrasion performance, etc.

Size	Load Index	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg)	Inflation Pressure (kpa)	Max Speed (km/h)
1500-20	153B	18	DW14L	18	TT	405	1310	3600	443	50
	164B	20	DW14L	18	TT	405	1310	5000	550	50
1500-21 (425/95-21)	154F	12	11.25	18	TT	405	1310	3750	475	80
	158F	14	11.25	18	TT	405	1310	4250	525	80



### W-16A E-2

- Applications: military vehicles, such as tank, armored car, and cross-country truck, as well as grader
- All-terrain tire applied on highway and generally paved road
- The unique pattern design and special compound design producing the overload, high-speed, and abrasion performance, etc.

Size	Load Index	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg)	Inflation Pressure (kpa)	Max Speed (km/h)
12.00-18 (320-457)	124J	8	8.00x18	23	TT	337	1084	1800	300	100
	132J	10	8.00x18	23	TT	337	1084	2000	360	100
	138J	14	8.00x18	23	TT	337	1084	2350	420	100
	141A8	8	9Ax18	23	TT	370	1128	2840	250	40
13.00-18 (340-457)	150A8	12	9Ax18	23	TT	370	1128	3350	350	40
	134E	10	7.00	18	TT	268	1035	2120	560	70
	141E	14	7.00	18	TT	268	1035	2575	770	70
9.00-20	145E	16	7.00	18	TT	268	1035	2800	880	70
	153E	18	8.00	19	TT	293	1085	3850	910	70
	136F	8	8.50	19	TT	335	1142	2240	400	80
11.00-20	148B	16	11.00	19	TT	370	1145	3150	420	50
12.00-20	153B	18	11.00	19	TT	370	1145	3650	530	50
12.5-20	156J	18	10.00	20	TT	367	1200	4000	600	100
	159J	20	10.00	20	TT	367	1200	4375	700	100
13.00-20	152J	16	10.00	24	TT	375	1265	3550	375	100
	156J	18	10.00	24	TT	375	1265	4000	425	100
14.00-20	156J	24	10.00	24	TT	375	1265	6000	625	100
	160J	16	11.25	28	TT	430	1495	4500	325	100
	171J	24	11.25	28	TT	430	1495	6150	475	100
16.00-24	156B	12	440x533	24	TT	530	1300	4050	400	50
	160B	14	440x533	24	TT	530	1300	4500	475	50
13.00-630-533	162B	16	440x533	24	TT	530	1300	4775	525	50
	10E	20	440x533	24	TT	530	1300	5980	570	50



### W-16B E-2

- Applications: military vehicles, such as missile transporting truck, tank, armored car, and cross-country truck, as well as grader
- All-terrain tire applied on highway and generally paved road
- The unique pattern design and special compound design producing the overload, high-speed, and abrasion performance, etc.

Size	Load Index	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg)	Inflation Pressure (kpa)	Max Speed (km/h)
15.5-20	168E	22	12.00	18	TT	440	1270	5800	700	70
18.00-24 (600-810)	178C	24	13.00	20	TT	500	1600	7500	450	60
12.00-400-533 (400-80-21)	142F	10	440x530	23	TT	418	1200	2650	300	80
12.00-500-508 (600-70-508)	160F	16	398x508	23	TT	500	1200	4500	440	80
12.00-530-533	160E	16	440x533	24	TT	530	1220	4500	475	70
15.00-600-635	169F	14	500x635	25	TT/TL	600	1500	5750	380	80
	173F	18	500x635	25	TT/TL	600	1500	6500	470	80
	176F	22	500x635	25	TT/TL	600	1500	7050	550	80
16.00-600-885	180F	24	500x635	27	TT/TL	600	1600	7900	440	80



### W-16C E-2

- Applications: military vehicles, such as tank, armored car, and cross-country truck
- All-terrain tire applied on highway and generally paved road
- The unique pattern design and special compound design producing the overload, high-speed, and abrasion performance, etc.

Size	Load Index	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load	Inflation Pressure	Max Speed
16.00-20	168E	28	10.00	22	TT	438	1343	5500	625	70
	170E	32	10.00	22	TT	438	1343	6000	675	70



### W-16D IND-3

- All-terrain tire suitable for military vehicles, such as nuclear material transporter
- Energy-saving rolling resistance, low temperature sensitivity, good stability, good traction, enhanced riding comfort
- Cushioned compound and shock resistance
- Reduced wear for longer life, improved mobility

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 40km/h	Inflation Pressure (kpa) 40km/h
355/65-15 (350-15)	24	9.75x15	23	TL	372	861	6000	1000

**TRACPRO668**


- Radial agri-tires suitable for high-powered tractors, harvesting and combined machines, carrying very high loads at low pressure
- Large selection of sizes ensuring the perfect fit for your equipment on road and fields, or even difficult and uneven terrain
- The extensive footprint area allowing even ground pressure distribution and minimizing soil compaction, then making TRACPRO668 also suitable for soil preparation, planting and soil treatments
- Comparing with the bias, the flexible strong carcass and the wide deep lugs producing minimal rolling resistance, more traction, lower vibration, higher driving comfort and longer life service
- Maximum resistance to impact and puncturing ensured by the high quality materials used

**95 Series**

Size	Load Index	Type	Rim	Inflated Dimensions (mm)	Speed	Load Capacity	Pressure	Replace
				SW OD	mph km/h	lbs kg	bar psi	
23095R32	128A8/128B	TL	W6	235 1265	25 40	3960 1800	4.0 58	
27095R32	136A8/136B	TL	W9	280 1345	25 40	4928 2240	4.0 58	
27095R38	140A8/140B	TL	W10	285 1480	25 40	5500 2500	4.0 58	
27095R48	144A8/144B	TL	W8	275 1570	25 40	6160 2800	4.0 58	

**85 Series**

Size	Load Index	Type	Rim	Inflated Dimensions (mm)	Speed	Load Capacity	Pressure	Replace
				SW OD	mph km/h	lbs kg	bar psi	
28085R24	115A8/112B	TL	W10	292 1098	25 40	2873 1215	1.6 23	11.2R24
28085R28	118A8/115B	TL	W10	292 1187	25 40	2904 1320	1.6 23	11.2R28
32085R24	122A8/119B	TL	W11	329 1154	25 40	3000 1500	1.6 23	12.4R24
32085R28	124A8/121B	TL	W11	329 1255	25 40	3530 1600	1.6 23	12.4R28
34085R24	125A8/122B	TL	W12	353 1188	25 40	3640 1650	1.6 23	13.6R24
34085R28	127A8/124B	TL	W12	353 1289	25 40	3860 1750	1.6 23	13.6R28
34085R38	133A8/130B	TL	W12	353 1543	25 40	4532 2060	1.8 26	13.6R38
38085R24	131A8/128B	TL	W13	390 1256	25 40	4290 1950	1.6 23	14.9R24
38085R28	133A8/130B	TL	W13	390 1357	25 40	4532 2060	1.6 23	14.9R28
42085R28	139A8/136B	TL	W16L	438 1425	25 40	5360 2430	1.6 23	16.9R28
42085R30	140A8/137B	TL	W15L	438 1475	25 40	5510 2500	1.6 23	16.9R30
42085R34	142A8/139B	TL	W15L	438 1578	25 40	5940 2650	1.6 23	16.9R34
42085R38	144A8/141B	TL	W15L	438 1679	25 40	6175 2900	1.6 23	16.9R38
46085R30	145A8/142B	TL	W16L	475 1544	25 40	6395 2900	1.6 23	18.4R30
46085R38	149A8/146B	TL	W16L	475 1747	25 40	7165 3250	1.6 23	18.4R38
52085R38	155A8/152B	TL	DW18L	536 1849	25 40	8545 3875	1.6 23	20.8R38
52085R42	157A8/157B	TL	DW18L	536 1952	25 40	9095 4125	1.6 23	20.8R42

**80 Series**

Size	Load Index	Type	Rim	Inflated Dimensions (mm)	Speed	Load Capacity	Pressure	Replace
				SW OD	mph km/h	lbs kg	bar psi	
48080R42	151A8/151B	TL	W16A	495 1850	25 40	7610 3450	1.6 23	18.4R42
48080R46	153A8/156B	TL	W16A	495 1964	25 40	8380 4250	2.4 35	
48080R50	150D	TL	DW15B	500 2045	40 65	9650 4375	2.4 35	

**75 Series**

Size	Load Index	Type	Rim	Inflated Dimensions (mm)	Speed	Load Capacity	Pressure	Replace
				SW OD	mph km/h	lbs kg	bar psi	
40075R38	138A8/135B	TL	DW14L	395 1565	25 40	5200 2360	1.6 23	15.5R38
62075R26	166A8	TL	DW20B	633 1690	25 40	11866 5300	3.2 46	23.1R26
65075R32	172A8	TL	DW20B	662 1817	25 40	13991 6300	3.2 46	24.5R32
65075R38	169D/166E	TL	DW23B	676 1940	40 65	12800 5800	2.4 35	
71075R32	177A8	TL	DW23B	735 1850	25 40	16095 7300	3.2 46	

**70 Series**

Size	Load Index	Type	Rim	Inflated Dimensions (mm)	Speed	Load Capacity	Pressure	Replace
				SW OD	mph km/h	lbs kg	bar psi	
38070R24	125A8/125B	TL	W12	370 1193	25 40	3640 1650	1.6 23	
38070R28	127A8/127B	TL	W12	370 1292	25 40	3950 1750	1.6 23	
42070R24	130A8/130B	TL	W13	415 1263	25 40	4200 1900	1.6 23	
42070R28	133D	TL	W13	415 1345	40 65	4542 2060	1.6 23	
48070R28	140D	TL	W15L	468 1415	40 65	5500 2500	1.6 23	
	145D/148A8	TL	W15L	468 1415	40 65	6390 2900	2.4 35	
48070R30	141D	TL	W15L	468 1474	40 65	5675 2575	1.6 23	
48070R34	143A8/143B	TL	W15L	468 1580	25 40	6005 2725	1.6 23	
48070R38	145A8/145B	TL	W15L	468 1684	25 40	6380 2900	1.6 23	
52070R34	148A8/148B	TL	W16L	520 1638	25 40	6930 3150	1.6 13	
52070R38	150D	TL	W16L	520 1740	40 65	7370 3350	1.6 23	
58070R38	155D	TL	W18L	584 1925	40 65	8525 3875	1.6 23	
60070R30	159D/155E	TL	DW18L	605 1808	40 65	9370 4250	1.6 23	
IF80070R20	159D	TL	DW21B	605 1610	40 65	9650 4375	1.6 23	
62070R42	166D	TL	DW20B	625 1935	40 65	11660 5300	2.4 35	
	166D	TL	DW20B	625 1945	40 65	11660 5300	2.4 35	
71070R38	166D	TL	DW23B	716 1959	40 65	11865 5300	1.6 23	
71070R42	179A8	TL	DW23B	725 2070	25 40	17085 7750	3.2 46	

**TRACPRO668**


- Radial agri-tires suitable for high-powered tractors, harvesting and combined machines, carrying very high loads at low pressure
- Large selection of sizes ensuring the perfect fit for your equipment on road and fields, or even difficult and uneven terrain
- The extensive footprint area allowing even ground pressure distribution and minimizing soil compaction, then making TRACPRO668 also suitable for soil preparation, planting and soil treatments
- Comparing with the bias, the flexible strong carcass and the wide deep lugs producing minimal rolling resistance, more traction, lower vibration, higher driving comfort and longer life service
- Maximum resistance to impact and puncturing ensured by the high quality materials used

**65 Series**

Size	Load Index	Type	Rim	Inflated Dimensions (mm)	Speed	Load Capacity	Pressure	Replace
				SW OD	mph km/h	lbs kg	bar psi	
48065R24	133D	TL	DW15L	479 1234	40 65	4532 2060	1.6 23	
48065R26	136D	TL	DW15L	479 1335	40 65	4940 2240	1.6 23	
54065R24	146A8	TL	DW16L	535 1312	25 40	6600 3000	2.4 35	
	140D	TL	DW16L	530 1312	40 65	5500 2500	1.6 23	
54065R28	142D	TL	DW16L	530 1413	40 65	5842 2650	1.6 23	
	149D/148E	TL	DW16L	530 1413	40 65	7160 3250	2.4 35	
54065R34	145D	TL	DW16L	530 1566	40 65	8390 2900	1.6 23	
54065R38	147D	TL	DW16L	530 1667	40 65	8778 3080	1.6 23	
	153D/150E	TL	DW16L	516 1709	40 65	8030 3650	2.4 35	
60065R26	147D	TL	DW18L	590 1491	40 65	6765 3075	1.6 23	
	154D/151E	TL	DW18L	590 1491	40 65	8250 3750	2.4 35	
60065R38	153D	TL	DW18L	590 1745	40 65	8075 3660	1.6 23	
65065R38	163D/159E	TL	DW20B	645 1811	40 65	10750 4875	2.4 35	
80065R32	178A8	TL	DW27B	800 1846	25 40	16535 7500	3.2 46	

**60 Series**

Size	Load Index	Type	Rim	Inflated Dimensions (mm)	Speed	Load Capacity	Pressure	Replace
				SW OD	mph km/h	lbs kg	bar psi	
90060R32	181A8	TL	DW30B	890 1900	25 40	18190 8250	3.2 46	

**SUPER FL168**


- Application: spreader, trailer and tanker on and off the road
- Radial flotation and transport tire with resistant structure providing excellent traction and perfect grip even in bends and when maneuvering
- The tread pattern design featuring excellent self-cleaning properties in all the conditions of use, and reducing soil compaction preserving the value of the crops

Size	Load Index	Type	Rim	Inflated Dimensions (mm)	Speed	Load Capacity	Pressure	Replace
				SW OD	mph km/h	lbs kg	bar psi	
56060R22.5	161D/172A8	TL	AG16.00	543 1244	44 70	9280 4210	58 4.0	
	181E	TL	AG16.00	543 1244	44 70	10200 4630	58 4.0	
60055R26.5	165D	TL	AG20.00	611 1333	44 70	10340 4700	58 4.0	
60055R26.5	177D	TL	AG20.00	611 1333	40 65	16090 7300	87 6.0	
(Steel Belts)	169D	TL	AG20.00	645 1389	44 70	11640 5290	58 4.0	
65055R26.5	178D	TL	AG20.00	645 1389	40 65	16530 7500	87 6.0	

**FLR3 R-3**


- Applications: combine harvester, spreader, sugar cane machinery, implement, agricultural trailer, tanker
- Flat and wide foot print suitable for flotation applications on soft soil, orchards, etc.
- Tread specially designed to give minimum ground disturbance
- Increased tread depth and strong carcass ensures long life

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)	Max Load (kg)	Inflation Pressure (kpa)
					SW OD	40km/h	40km/h
23-1.26	12	DW20	28	TT/TL	587	1580	3610
	14	DW20	28	TT/TL	587	1580	3970
	16	DW20	28	TT/TL	587	1580	4300
23-1.30	12	DW20	17.4	TL	587	1683	3450
	16	DW20	17.4	TL	587	1683	4570
28L-26	12	DW25B/DW23B	27	TL	714	1560	3765
	16	DW25B/DW23B	27	TL	714	1560	4605
	20	DW25B/DW23B	27	TL	714	1560	5315
24.5-32	12	DW21	28	TL	623	1775	4390
	16	DW21	28	TL	623	1775	4984
30.5L-32	12	DW27	29	TL	750	1790	4210
	16	DW27	29	TL	750	1790	4745
	20	DW27	29	TL	750	1790	5370



### IMPT F-3

- Applications: implement machinery, hay harvester, baler, agri-trailer, multipurpose truck
- Ideal tires for modern farming, suitable for both on and off-the-road applications
- Low section tires, offering high load capacity with minimum soil compaction & great transportation properties
- Optimum tread arc delivering fullest possible footprint

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)	Max Load (kg)	Inflation Pressure (kPa)
					SW OD	40km/h	40km/h
100/80-12	8	9.00	9	TL	264 710	1240	310
	12	9.00	9	TL	264 710	1650	390
	16	9.00	9	TL	264 710	2050	490
100/75-15.3	10	9.00	9	TL	264 760	1525	390
	16	9.00	9	TL	264 760	2110	525
	12	9.00	10	TL	290 845	2145	410
11.5/80-15.3	16	9.00	10	TL	290 845	2575	475
	18	9.00	10	TL	290 845	2760	510
	14	9.00	10	TL	307 889	2425	410
12.5/80-15.3	16	9.00	10	TL	307 889	2680	450
	18	9.00	10	TL	307 889	2940	475
	16	11.00	11	TL	336 890	2750	490
130/65-18	18	11.00	11	TL	336 890	2945	550



### IMPT5 F-3

- Applications: implement machinery, hay harvester, baler, agri-trailer, multipurpose truck
- Ideal tires for modern farming, suitable for both on and off-the-road applications
- Low section tires, offering high load capacity with minimum soil compaction & great transportation properties
- Optimum tread arc delivering fullest possible footprint
- Design for Implement Machinery

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)	Max Load (kg)	Inflation Pressure (kPa)
					SW OD	40km/h	40km/h
15.0/55-17	10	13.00	12	TL	391 850	2120	360
	12	13.00	12	TL	391 850	2360	420
	14	13.00	12	TL	391 850	2575	490
	18	13.00	12	TL	391 850	3250	650



### IMPT7 F-3

- Applications: implement machinery, hay harvester, baler, agri-trailer, multipurpose truck
- Ideal tires for modern farming, suitable for both on and off-the-road applications
- Low section tires, offering high load capacity with minimum soil compaction & great transportation properties
- Optimum tread arc delivering fullest possible footprint

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)	Max Load (kg)	Inflation Pressure (kPa)
					SW OD	40km/h	40km/h
19.0/45-17	10	17.00	12	TL	491 866	2360	300
	14	17.00	12	TL	491 866	2800	390
	18	17.00	12	TL	491 866	4000	450
500/50-17	10	16.00	12	TL	500 945	2900	270
	14	16.00	12	TL	500 945	3650	360
	16	16.00	12	TL	500 945	3975	440
	18	16.00	12	TL	500 945	4125	480
400/60-15.5	10	AG13.00	12	TL	400 945	2240	360
	14	AG13.00	12	TL	400 945	2725	490
	18	AG13.00	12	TL	400 875	3450	600



### SCI3 I-3

- Applications: agricultural implement & trailer, tank, spreader, forestry trailer, sugar cane harvester, both on and off-the-road
- Flotation implement tires designed for high load capacities at low inflation pressures, minimising soil compaction and preventing damage to crops

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)	Max Load (kg)	Inflation Pressure (kPa)
					SW OD	40km/h	40km/h
400/60-15.5	14	13.00	25	TL	404 875	3725	200
800/50-22.5	16	20.00	25	TL	600 1170	5150	280
	18	20.00	25	TL	600 1170	5600	300
700/50-26.5	12	24.00	26	TL	700 1380	5800	180
	16	24.00	26	TL	700 1380	6700	240
710/45-26.5	12	AG24.00	26	TL	710 1380	5900	180
	16	AG24.00	26	TL	710 1380	6800	240
750/60-30.5	16	24.00x30.5	25	TL	750 1670	8500	220



### FORESTRY LS-2

- Application: logging skidder machines
- Steel belted construction with heavy duty nylon casing giving puncture proof performance & longer tire life
- Robust lug design with optimum angle & wider width providing excellent traction
- Specially designed cut resistance tread compound providing excellent cut & chip resistance under severe terrain conditions
- Thicker sidewall, stronger bead & rim guard protecting from external damages

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)	Max Load (kg)	Inflation Pressure (kPa)
					SW OD	30km/h	30km/h
169-30	10	W15L	48	TT/TL	210 1510	2575	210
	16	W15L	48	TT/TL	210 1510	3210	300
184-36	10	DM16A	50	TT/TL	465 1475	2575	170
	16	DM16A	50	TT/TL	465 1475	3500	280
184-30	10	DM16A	50	TT/TL	465 1475	2725	170
	16	DM16A	50	TT/TL	465 1475	3600	280
184-34	12	DM16A	50	TT/TL	465 1680	3250	210
	16	DM16A	50	TT/TL	465 1680	3700	280
231-26	14	DM20A	53	TT/TL	590 1630	4125	210
	16	DM20A	53	TT/TL	590 1630	4450	240
245-32	16	DH21	55	TT/TL	625 1830	5000	210
	20	DH21	55	TT/TL	625 1830	5800	280
26L-26	18	DM25A	55	TT/TL	715 1645	4800	210
	20	DM25A	55	TT/TL	715 1645	5150	240
305L-32	18	DH27	55	TT/TL	775 1845	5950	210
	20	DH27	55	TT/TL	775 1845	6530	240
	26	DH27	55	TT/TL	775 1845	7100	280
	DH36L-32	20	DH32	58	TT/TL	905 2004	6530
73x44.00-32	26	DH32	58	TT/TL	905 2004	8750	280
	16	DH36	67	TL	1153 1870	6900	280
20	DH36	67	TL	1153 1870	8000	340	



### QZ-50Z

- Applications: tractor front, loader front, mower front
- Strong nylon carcass ensuring good performance
- Three-ribs front wheel tires, designed for easy steering

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)	Max Load (kg)	Inflation Pressure (kPa)
					SW OD	40km/h	40km/h
6.50-20	8	5.00F	16	TT	180 860	865	420



### QZ-60Z F-2

- Applications: tractor front for field operations and regular transportation
- Self-cleaning tread for positive steering
- Sturdy shoulder bard offering excellent sidewall protection
- Wide tread area guarantees longer life

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)	Max Load (kg)	Inflation Pressure (kPa)
					SW OD	30km/h	30km/h
400-16	4	3.00D	14	TT	110 640	280	320
	6	3.00D	14	TT	110 640	300	340
450-16	6	3.00D	14	TT	122 655	462	450
500-15	6	4.00J	14	TT	140 665	465	420
500-16	6	4.00E	15	TT	130 655	550	420
550-16	6	4.00E	15	TT	150 710	525	370
600-16	6	4.00E	15	TT	160 740	560	340
650-16	6	4.50E	16	TT	175 780	615	310
650-20	8	5.00F	16	TT	160 860	865	420
750-16	8	5.50F	20	TT	205 810	870	370


**QZ-701 R-2**

- Tractor tire suitable for soil tillage applications, designed for providing maximum performance on wet and moist soil
- Offering superior grip and enhanced self-cleaning features
- Tread and sidewall rubber compounds fight off acid and ozone, producing long-life service
- Strong casing for excellent stability and safety to the operator

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 40km/h	Inflation Pressure (kPa) 40km/h
11.2-24	8	W10	63.5	TT	285	1105	1225	240
12.4-24	8	W11	67	TT	315	1182	1415	230
12.4-38	8	W11	67	TT	315	1500	1750	230
13.6-38	8	W12	70	TT	345	1600	1910	210
14.9-24	8	W13	73	TT	390	1305	1760	180
16.9-30	10	W15L	76	TT/TL	430	1530	2455	200
16.9-34	10	W15L	76	TT/TL	430	1600	2605	200
18.4-30	10	W16L	81	TT/TL	467	1570	2815	180
18.4-34	10	W16L	81	TT/TL	467	1702	2990	180
18.4-38	10	W16L	81	TT/TL	467	1775	3165	180
19.5L-24	12	DW16	76	TT/TL	495	1357	2145	210
20.8-38	10	W18L	85	TT/TL	530	1855	3475	160
23.1-26	12	DW20	89	TT/TL	587	1692	3610	170
23.1-30	14	DW20	89	TT/TL	587	1770	4210	200
23.1-34	14	DW21	89	TT/TL	587	1870	4450	200
24.5-32	10	DW21	89	TT/TL	623	1832	3570	138
28L-26	14	DW25	89	TT/TL	715	1672	4250	170
20.8-42	14	W19A	85	TT/TL	528	1988	4500	200


**QZ-701A R-2**

- Extra deep tread specially designed to get excellent traction on wet and sticky soil with excellent self-cleaning properties, preventing mud clogging between the tugs
- Sidewall rubber preventing weather cracking
- Tough tread compound to resist fast wear

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 40km/h	Inflation Pressure (kPa) 40km/h
650-16	8	4.50E	65	TT	165	830	665	250
750-16	8	5.50F	75	TT	195	890	750	250
83-20	8	W7	75	TT	210	950	790	270
83-24	8	W7	75	TT	210	1050	910	270
95-24	10	W8	75	TT	240	1150	1210	320
11.2-24	10	W10	80	TT	285	1205	1380	320
12.4(11.2)	10	W10	85	TT	285	1255	1495	280
12.4-28	10	W11	85	TT	315	1315	1745	280
11-32	10	W10	87	TT	305	1460	1080	160


**QZ-702A R-1/HF-2**

- Applications: combine harvester, high-power tractor, monster truck
- High flotation capability along with low soil compaction and excellent traction in the field
- High load capacity to improve modern farmers' requirements in terms of productivity
- Flexible sidewall rubber compounded with super-tough tread rubber for superior ride, snag resistance and long wear
- Bead-and-rim flange protector reducing downtime by keeping out debris

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg)	Inflation Pressure (kPa)	Max Speed (km/h)
302L-32	16	DH27	50	TT/TL	775	1820	4745	140	30
	18	DH27	50	TT/TL	775	1820	5370	170	30
	20	DH27	50	TT/TL	775	1820	5950	210	30
68.4300-25	10	36.00	38	TL	1054	1702	4500	170	40
	12	36.00	38	TL	1054	1702	5000	210	40
	16	36.00	38	TL	1054	1702	6100	290	40


**QZ-702 R-1**

- Applications: tractor, excavator, trailer, harvester, spreader, soil tillage and spraying machines
- Large selection of sizes ensures the perfect fit for your equipment
- Dual angled lugs bracing for better traction, more stability and less squirm
- Dual rubber compounds — flexible rubber on the sidewalls to resist weather cracking plus super-tough rubber on the tread for long wear
- Bead-and-rim flange protector reducing downtime by keeping out debris

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm) SW	OD	Max Load (kg) 30km/h	Inflation Pressure (kPa) 30km/h
500-12	4	3.50-B	22	TT	145	590	280	200
600-12	6	4.50-B	22	TT	165	640	405	250
600-16	6	4.50-E	22	TT	165	745	495	250
750-16	8	5.50-F	23	TT	205	810	700	240
550-17	8	4.00-E	22	TT	165	745	440	250
750-20	8	5.50-F	24	TT	205	910	880	280
83-20	8	W7	30	TT	210	895	695	240
	8	W7	30	TT	210	895	810	280
83-24	8	W7	30	TT	210	995	920	280
95-20	8	W6	33	TT	240	950	955	280
95-24	8	W6	30	TT	240	1050	1110	280
11.2-24	8	W10	33	TT	285	1105	1225	240
11.2-28	8	W10	33	TT	285	1205	1325	240
	10	W10	33	TT	285	1205	1600	300
	12	W10	33	TT	285	1205	1675	360
12-38	8	DW11	35	TT	330	1575	1570	140
	10	DW11	35	TT	330	1575	1800	220
12.4-24	8	W11	38	TT	315	1160	1200	170
	8	W11	38	TT	315	1180	1415	230
	10	W11	38	TT	315	1180	1630	280
12.4-28	8	W11	38	TT	315	1260	1510	230
	10	W11	38	TT	315	1260	1745	280
12.4-38	8	W11	38	TT	315	1665	1750	230
	10	W11	38	TT	315	1665	2020	280
136-24	8	W12	37	TT	345	1210	1545	210
	10	W12	37	TT	345	1210	1790	250
136-28	8	W12	38	TT	345	1310	1500	180
	10	W12	38	TT	345	1310	1810	250
136-38	8	W12	38	TT	345	1565	1900	210
	10	W12	38	TT	345	1565	2215	250
149-24	8	W13	35	TT	378	1265	1760	180
	10	W13	35	TT	378	1265	1990	230
149-28	8	W13	39	TT/TL	378	1315	1820	180
	10	W13	39	TT/TL	378	1315	2050	230
149-28	8	W13	38	TT/TL	360	1365	1880	180
	10	W13	38	TT/TL	360	1365	2120	230
169-24	10	W15L	39	TT/TL	430	1335	2230	200
	12	W15L	39	TT/TL	430	1335	2360	260
169-28	10	W15L	39	TT/TL	430	1410	2300	200
	12	W15L	39	TT/TL	430	1410	2450	260
169-28	10	W15L	39	TT/TL	430	1435	2380	200
	12	W15L	39	TT/TL	430	1435	2655	260
169-30	10	W15L	40	TT/TL	430	1485	2455	200
	12	W15L	40	TT/TL	430	1485	2730	240
169-34	8	W15L	39	TT/TL	430	1585	2380	170
	10	W15L	39	TT/TL	430	1585	2605	200
	12	W15L	39	TT/TL	430	1585	2820	230
169-36	8	W15L	39	TT/TL	430	1685	2520	170
	10	W15L	39	TT/TL	430	1685	2700	200
	12	W15L	39	TT/TL	430	1685	2880	230
184-26	10	DW16	38	TT/TL	467	1450	2645	180
	12	DW16	38	TT/TL	467	1450	2985	230
184-28	8	W16L	38	TT/TL	467	1500	2130	140
	10	W16L	38	TT/TL	467	1500	2750	180
	12	W16L	38	TT/TL	467	1500	3135	220
184-30	8	W16L	38	TT/TL	467	1550	2415	140
	10	W16L	38	TT/TL	467	1550	2915	180
	12	W16L	38	TT/TL	467	1550	3180	230
184-34	8	W16L	38	TT/TL	467	1655	2565	140
	10	W16L	38	TT/TL	467	1655	2990	180
	12	W16L	38	TT/TL	467	1655	3375	230
184-38	10	W16L	41	TT/TL	467	1755	3165	180
	12	W16L	41	TT/TL	467	1755	3575	230
208-38	10	W18L	42	TT/TL	530	1835	3475	160
	12	W18L	42	TT/TL	530	1835	4000	200
231-30	12	DW20	42	TT/TL	587	1705	3650	170
	16	DW20	42	TT/TL	587	1705	4570	230
245-32	12	DW21	42	TT/TL	622	1865	4360	170
	16	DW21	42	TT/TL	622	1865	4994	210
28L-26	14	DW25A	42	TT/TL	715	1615	4250	170
	16	DW25A	42	TT/TL	715	1615	4605	200


**QZ-702C R-1/HF-2**

- Applications: high-powered tractor, and monster truck
- The high flotation agricultural tires, large ground contact area, low-pressure ratio on the ground and less damage to soil and sapling
- Tread bars of certain angle give good self-cleaning action, excellent traction and side slippage-proof
- Deep tread design and cut-resistant tread compound give extended service life

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)
					SW	OD	40km/h	40km/h
68-4300-25	10	38.00	38	TL	1054	1702	4500	170
	12	38.00	38	TL	1054	1702	5000	210
	16	38.00	38	TL	1054	1702	6100	290


**QZ-702N R-1**

- Applications: tractor, harvester, spreader
- More intensive lugs providing better traction, self-cleaning properties and stability
- The ideal partner used even on the harshest ground conditions

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)
					SW	OD	30km/h	30km/h
18442	12	W-16A, DD16	40	TT/TL	467	1857	3000	180
20842	12	W18A, DD18	42	TT/TL	528	1935	3350	150
23134	10	DW20B, DW20	42	TT/TL	602	1798	2900	110
	12	DW20B, DW20	42	TT/TL	602	1798	3350	150


**QZ-703**

- Applications: tractor trailer, spreader, harvester, agricultural implements
- Designed especially for agricultural machines with load capacity 9-12 tons
- Tough nylon-cord body for durability and long wear

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)
					SW	OD	30km/h	30km/h
15565-19	12	W13	15	TT	395	980	2890	310
16570-18	14	W13	15	TT	425	1065	3650	410


**QZ-704 F-2**

- Applications: 2WD tractor front in soil tillage applications
- Particularly suitable for all operations requiring a high level of handling
- Providing high flotation capability contributing to reduce soil compaction

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)
					SW	OD	30km/h	30km/h
100-16	10	W6L	16	TT/TL	275	910	1325	340
110-16	10	W10L	16	TT/TL	315	970	1350	345
11L-15	8	8.00	21	TT/TL	280	810	950	300


**QZ-705 R-1**

- Applications: tractor, harvester, spreader
- Ideal for use on soft soil, chards and similar applications
- Specially engineered tread design providing high flotation
- Increased tread depth and strong carcass ensuring good stability, traction, self-cleaning properties and long service life

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)
					SW	OD	30km/h	30km/h
231-26	12	DW20	34	TT/TL	587	1805	3610	170
	14	DW20	34	TT/TL	587	1805	3970	200
	16	DW20	34	TT/TL	587	1805	4300	230


**QZ-706 I-1**

- Applications: 2WD tractor front in soil tillage and transport applications
- This tire ensuring a high level of handling comfort
- Available in different versions to specifically meet end-user requirements in terms of cut and chip resistance and heavy-duty service

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)
					SW	OD	30km/h	30km/h
900-16	10	6.00F	12	TT	235	850	1445	325
100-16	10	6.00F	12	TT	276	894	1850	320


**QZ-707 R-1**

- Applications: pivot irrigator
- Round-shaped lugs to reduce soil damage and protect the precious crops
- Flexible sidewall dual rubber compounds combined with super-tough tread rubber for long wear and resistance to weather checking

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)
					SW	OD	40km/h	40km/h
112-38	4	W10	30	TT/TL	285	1485	950	120


**QZ-708 R-1**

- Applications: pivot irrigator
- Round-shaped lugs to reduce soil damage and protect the precious crops
- Flexible sidewall dual rubber compounds combined with super-tough tread rubber for long wear and resistance to weather checking

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)
					SW	OD	40km/h	40km/h
112-24	4	W10	28	TT/TL	285	1105	845	130
	6	W10	28	TT/TL	285	1105	1045	180
	8	W10	28	TT/TL	285	1105	1225	240
14.9-24	4	W13	30.5	TT/TL	378	1265	1210	100
	6	W13	30.5	TT/TL	378	1265	1510	140
	8	W13	30.5	TT/TL	378	1265	1760	180


**QZ-709A I-1**

- Applications: free-rolling wheels used in harvesting machines, hay baler, bale rack, seeder, windrower, and fertilizer/manure spreader
- Multi rib, low section I-1 tires designed to provide high flotation with minimum soil compaction with excellent load distribution
- Cut-resistant sidewall reducing downtime, shock-fortified nylon-cord body resisting impacts
- Specially fortified rubber resisting stubble puncture and tire erosion, and stubble stopper construction available in certain sizes

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)
					SW	OD	40km/h	40km/h
900-16	10	6.00	9	TT	234	848	1480	360


**QZ-709 I-1**

- Applications: harvesting machines, hay baler, bale rack, seeder, windrower, and fertilizer/manure spreader on and off-the-road services
- Multi rib, low section I-1 tires designed to provide high flotation with minimum soil compaction with excellent load distribution
- Cut-resistant sidewall reducing downtime, shock-fortified nylon-cord body resisting impacts
- Specially fortified rubber resisting stubble puncture and tire erosion, and stubble stopper construction available in certain sizes

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		IMP@40km/h		SL IMP@65km/h	
					SW	OD	Max Load (kg)	Inflation Pressure (kPa)	Max Load (kg)	Inflation Pressure (kPa)
4.00-18	4	3.00D	4.5	TT/TL	112	670	480	275	480	275
5.00-15	4	3.00D	8.5	TT/TL	130	640	430	225	430	225
5.90-15	4	4.50E	8.5	TT/TL	155	685	515	250	515	250
6.00-16	6	4.00E	8.5	TT/TL	158	710	685	275	685	275
6.40-15	6	4.5K	8.5	TT/TL	163	685	670	275	670	275
6.50-16	6	4.50E	7	TT/TL	173	735	775	275	775	275
6.70-15	4	4.5K	8.5	TT/TL	170	705	545	195	545	195
6	6	4.5K	6.5	TT/TL	170	705	730	275	730	275
7.50-14	4	5.50F	7.5	TT/TL	194	688	615	190	615	190
6	6	5.50F	7.5	TT/TL	194	688	805	275	805	275
7.50-16	8	5.50F	8.5	TT/TL	203	808	1100	325	1100	325
7.60-15	8	5.50F	8.5	TT/TL	200	721	950	360	950	360
7.50-20	4	5.50F	7.5	TT/TL	203	855	775	150	775	150
8	8	5.50F	7.5	TT/TL	203	855	980	225	980	225
8	8	5.50F	7.5	TT/TL	203	855	1185	300	1185	300
9.00-10	4	6LB	8.5	TT/TL	235	696	670	170	670	170
8	8LB	8.5	TT/TL	235	696	880	225	880	225	
9.00-16	12	8LB	8.5	TT/TL	235	696	1070	300	1070	300
8	8LB	8.5	TT/TL	235	696	1215	275	1215	275	
8	8LB	8.5	TT/TL	235	696	1445	300	1445	300	
9.00-24	8	V8	8.5	TT/TL	272	1095	1590	250	1590	250
12	V8	8.5	TT/TL	272	1095	1900	300	1900	300	
10.00-15	8	8LB	8	TT/TL	278	855	1425	240	1425	240
12	8LB	8	TT/TL	278	855	1550	300	1550	300	
10.5/80-18	10	V8-18	6.5	TT	278	885	1950	370	1950	370
12	V8-18	6.5	TT	278	885	2175	410	2175	410	
11.25-24	8	W10	9.5	TT/TL	325	1170	1860	200	1860	200
12	W10	9.5	TT/TL	325	1170	2380	330	2380	330	
11.25-28	8	W10	9.5	TT/TL	325	1275	1925	200	1925	200
12	W10	9.5	TT/TL	325	1275	2430	330	2430	330	
8.5L-14	6	8KB	9	TT/TL	215	720	850	220	850	220
8	8KB	9	TT/TL	215	720	1020	300	1020	300	
9.5L-14	8	8D	8	TT/TL	239	737	1050	280	1050	280
12	8D	8	TT/TL	239	737	1360	360	1360	360	
9.5L-16	8	8LB	6	TT/TL	240	785	1100	280	1100	280
12	8LB	6	TT/TL	240	785	1510	360	1510	360	
11L-14	8	8K	6	TT/TL	260	752	1080	220	1080	220
12	8K	6	TT/TL	260	752	1390	330	1390	330	
11L-15	8	V8L	6	TT/TL	260	775	1130	220	1130	220
12	V8L	6	TT/TL	260	775	1485	330	1485	330	
11L-16	8	V8L	6	TT/TL	275	800	1175	220	1175	220
12	V8L	6	TT/TL	275	800	1505	330	1505	330	
12.5L-15	12	10.00	6	TT/TL	317	825	1745	330	1745	330
16	10.00	6	TT/TL	317	825	2165	390	2165	390	
12.5L-16	12	10.00	10	TL	317	850	1800	330	1800	330
16	10.00	10	TL	317	850	2220	390	2220	390	

**QZ-709M I-1**

- Applications: tank, wagon and trailer for on and off-the-road services, as well as the steer tires on combine-harvester
- Multi rib, low section I-1 tires designed to provide high flotation with minimum soil compaction with excellent load distribution
- Cut-resistant sidewall reducing downtime, shock-fortified nylon-cord body resisting impacts
- Specially fortified rubber resisting stubble puncture and tire erosion, and stubble stopper construction available in certain sizes

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		IMP@40km/h		SL IMP@65km/h	
					SW	OD	Max Load (kg)	Inflation Pressure (kPa)	Max Load (kg)	Inflation Pressure (kPa)
14L-16.1	8	16.1x11LB	10	TT/TL	355	940	1575	170	1575	170
12	16.1x11LB	10	TT/TL	355	940	2090	280	2090	280	
14	16.1x11LB	10	TT/TL	355	940	2345	330	2345	330	
18	16.1x11LB	10	TT/TL	355	940	2855	410	2855	410	
16.5L-16.1	10	16.1x14LB	11	TT/TL	420	1025	2380	220	2380	220
14	16.1x14LB	11	TT/TL	420	1025	2900	300	2900	300	
16	16.1x14LB	11	TT/TL	420	1025	3330	360	3330	360	
20	16.1x14LB	11	TT/TL	420	1025	3500	410	3500	410	
19L-16.1	10	16.1x16LB	12	TT/TL	483	1085	2725	190	2725	190
14	16.1x16LB	12	TT/TL	483	1085	3175	250	3175	250	
8	16.1x16LB	12	TT/TL	483	1085	3625	300	3625	300	
20	16.1x16LB	12	TT/TL	483	1085	3650	330	3650	330	
10	16.1x18LB	14	TT/TL	545	1130	3000	170	3000	170	
14	16.1x18LB	14	TT/TL	545	1130	3550	220	3550	220	
16	16.1x18LB	14	TT/TL	545	1130	4000	300	4000	300	
20	16.1x18LB	14	TT/TL	545	1130	4300	330	4300	330	
49-17	20	13.00	11	TT/TL	425	1200	3000	375	3000	375
24	13.00	11	TT/TL	425	1200	365	365	3300	365	
28	13.00	11	TT/TL	425	1200	3600	400	3600	400	


**QZ-710 R-1**

- Applications: tractor, harvester, spreader
- Strong casing to carry heavy loads
- Dual angled lugs to give better traction in the field and provide comfortable ride on road
- More tensile lugs providing uniform destruction of load
- Optimum tread depth and special tread compound for higher mileage

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)	Max Load (kg)	Inflation Pressure (kPa)	
					SW	OD	40km/h	
11.2-20	8	W10	38	TT	285	1005	1085	240
15.5-38	8	W14L	38	TT	395	1570	2060	180
28.1-28	12	DV2.5	46	TT	750	1750	4200	170


**QZ-711 R-1**

- Applications: harvester, tractor, sprayer and trailer in harvesting, soil tillage and spraying applications
- Special pattern and casing design producing large ground contact area for minimum soil compaction, low ground pressure, low rolling resistance on soft ground, good lateral stability

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)	Max Load (kg)	Inflation Pressure (kPa)	
					SW	OD	40km/h	
9.5-32	8	V8	28	TT	240	1250	1260	280


**PNLMAX**

- Applications: loader & earthmover used in the harsh conditions, such as construction and mining areas
- Super strong press-on solid tire with special compounds

Size	Pattern	Rim	Section Width (mm)	Overall Diameter (mm)	Load capacity(kg)				Weight kg		
					10km/h		26km/h				
					Loading	Rotation	Loading	Rotation			
20.5/70-16	E3/L-3	9.50	285	890					192.0		
20.5/70-16 Plus	E3/L-3	9.50	336	910					149.0		
8.25-16	E3/L-3	6.50	216	820					93.8		
14.00-20	E-4	10.00	319	1335	11865	9490			326.0		
14.00-24	E-4	14.00/1.5	398	1310	13000	10500	11000	8000	8500	7000	443.5
20-25	E-4	17.00	485	1350	15000	11000	13000	8500	10000	7500	743.0
23.5-25	E-4	19.50/2.5	527	1540	19500	14500	17000	13000	13500	11500	915.0
26.5-25	L-5	22.00	650	1735	39300	31400	37400	28100	35400	26600	1406.0



### POSTR&POSSM

- Applications: lifter or forklift in tough working condition
- Super strong press-on solid tire with special compounds

Size (inch)	Size (mm)	Pattern	Load capacity (Kg)		Balance forklift		Other Industrial 16km/h
			10km/h		16km/h		
			Drive	Steer	Drive	Steer	
10*5.6/1.4	254*127*158.8	POSTR/POSSM	1292	1156	1238	1142	983
10*5.6/1.2	254*127*165.1	POSTR/POSSM	1278	1142	1224	1129	988
10/12*6.5	267*152*127	POSTR/POSSM	1761	1564	1686	1564	1360
13/12*5.1/2*8	343*140*203.2	POSTR/POSSM	1904	1700	1822	1686	1489
14*5.10	356*127*254	POSTR/POSSM	1680	1518	1616	1506	1242
14*4/2*9	356*114*203.2	POSTR/POSSM	1482	1319	1414	1306	1142
15*5.11/1.4	381*127*285.8	POSTR/POSSM	3415	3585	2905	3075	2390
15*5.11/1.4	381*152*285.8	POSTR/POSSM	3675	3955	3305	3420	2720
15*7.11/1.4	381*178*285.8	POSTR/POSSM	4325	4335	3715	3755	3040
15*9.11/1.4	381*202*285.8	POSTR/POSSM	4775	4580	4125	4090	3360
15/12*5.10	394*127*254	POSTR/POSSM	1470	1210	1315	1100	1050
15/12*6.10	394*152*254	POSTR/POSSM	1870	1530	1665	1400	1330
16*4/12*12	406*127*305	POSTR/POSSM	1890	1660	1742	1560	1400
16*5.10/1.2	406*127*266.7	POSTR/POSSM	1400	1250	1340	1240	1080
16*6.10/1.2	406*152*266.7	POSTR/POSSM	1780	1580	1700	1570	1370
16*7.10/1.2	406*178*266.7	POSTR/POSSM	2325	1910	2070	1740	1660
16/14*5.11/1.4	413*127*285.8	POSTR/POSSM	1530	1250	1360	1145	1090
16/14*6.11/1.4	413*152*285.8	POSTR/POSSM	1920	1580	1715	1440	1370
18*5.12/1.8	457*127*308	POSTR/POSSM	2081	1850	1986	1836	1591
18*5.12/1.8	457*152*308	POSTR/POSSM	2652	2396	2530	2398	2040
18*7.12/1.8	457*178*308	POSTR/POSSM	3229	2870	3087	2856	2475
18*9.12/1.8	457*202*308	POSTR/POSSM	2790	2480	2670	2470	2150
18*9.12/1.8	457*222*308	POSTR/POSSM	4372	3890	4175	3862	3359
21*7.15	533*178*381	POSTR/POSSM	2870	2380	2550	2360	2050
21*8.15	533*203*381	POSTR/POSSM	4270	3801	4080	3781	3291
21*9.15	533*229*381	POSTR/POSSM	4923	4379	4706	4352	3794
22*7.16	559*178*406.4	POSTR/POSSM	2975	2450	2650	2230	2125
22*8.16	559*202*406.4	POSTR/POSSM	4434	3944	4230	3917	3407
22*9.16	559*229*406.4	POSTR/POSSM	5100	4542	4882	4515	3930
22*10.16	559*254*406.4	POSTR/POSSM	5780	5141	5522	5114	4447
22*12.16	559*305*406.4	POSTR/POSSM	7120	6338	6800	6297	5481
28*12.22	711*305*558.8	POSTR	6527	7589	8146	7548	6562



### PNSKS

- Applications: skid steer, lifter or forklift in tough working condition
- Super strong press-on solid tire with special compounds
- Flexible mounting with rims

Size with Rim	Size without Rim	Standard Size	Pattern	Standard Rim	Diameter		Load 10km/h	Weight
					mm	mm		
31*6*10	31x10-20	10-16.5	PNSKS	7.5-20	740	235	3415	100.2
33*6*11	33x12-20	12-16.5	PNSKS	8.00-20	838	276	4075	125.0
36*7*11		14-17.5	PNSKS	10.5	914	276	5650	178.0
40*9*13		15-19.5	PNSKS	11.75	1016	336	7545	275.0
36*7*13		16/70-20	PNSKS	13.00	980	330	6320	209.0



### PNSH05

- Applications: lifter or forklift in tough working condition
- Super strong press-on solid tire with special compounds

Size	Weight kg	Rim	Overall Diameter (mm)	Section Width (mm)	Load capacity (kg)				Other Industrial 16km/h		
					10km/h		16km/h				
					Load	Steer	Load	Steer			
21*8-9	334	6	507	184	2810	2250	2715	2035	2530	1895	1940
23*9-10	464	6.5	575	193	4005	3205	3845	2895	3605	2705	2765
27*10-12	674	8	655	235	4465	3570	4315	3235	4020	3015	3080



### PNST6-W/PNST6

- Applications: lifter or forklift in tough working condition
- Super strong press-on solid tire with special compounds
- PNSH01-W tires to eliminate the marking issue on the ground

Size	Weight kg	Rim	Section Width (mm)	Overall Diameter (mm)	Load capacity (kg)		Balance forklift		Other Industrial 16km/h					
					10km/h		16km/h							
					Drive	Steer	Drive	Steer						
5.00-8	18.0	3.00	126	469	1210	970	1175	890	1095	820	640			
6.00-8	27.8	4.00	140	545	1920	1535	1855	1390	1730	1295	1325			
6.50-10	36.6	5.00	157	597	2840	2110	2545	1910	2370	1780	1820			
7.00-9	32.2	5.00	170	578	2370	2015	2805	1925	2370	1750	1785			
7.00-12	45.0	5.00	168	683	3015	2410	2910	2185	2710	2035	2075			
8.15-15 (28*9-15)	63.0	7.00	207	706	4090	3270	3945	2960	3675	2755	2820			
8.25-12	64.8	6.50	206	735	3328	2660	3215	2410	2955	2245	2295			
8.25-15	68.8	6.50	205	847	4940	3950	4765	3575	4440	3330	3045			
250-15	66.0	7.00	220	735	4366	3400	4220	3160	3930	2955	3010			
					7.50	226	735	4366	3400	4220	3160	3930	2955	3010
300-15	99.0	8.00	258	838	5990	4700	5780	4335	5380	4037	4130			
18*8-9	20.8	4.33	154	457	2350	1890	2265	1700	2110	1585	1620			
15x4.5-8	9.6	3.00	106	380	905	725	675	655	805	605	625			



### PNSH01-W/PNSH01

- Applications: lifter or forklift in tough working condition
- Super strong press-on solid tire with special compounds
- PNSH01-W tires to eliminate the marking issue on the ground

Size	Weight kg	Rim	Overall Diameter (mm)	Section Width (mm)	Load capacity (kg)		Balance forklift		Other Industrial 16km/h					
					10km/h		16km/h							
					Drive	Steer	Drive	Steer						
4.00-8	12.2	3.00	423	115	1055	845	1020	765	950	715	730			
					3.75	423	115	1050	845	1020	765	950	715	730
5.00-8	18.0	3.00	469	126	1210	970	1175	890	1095	820	640			
6.00-9	27.8	4.00	545	140	1920	1535	1855	1390	1730	1295	1325			
6.50-10	36.6	5.00	597	157	2840	2110	2545	1910	2370	1780	1820			
7.00-9	32.2	5.00	578	170	2370	2015	2805	1925	2370	1750	1785			
7.00-12	45.0	5.00	683	168	3015	2410	2910	2185	2710	2035	2075			
7.00-15	68.8	5.50	759	178	3590	2870	3465	2600	3225	2420	2475			
					6.00	759	178	3590	2870	3465	2600	3225	2420	2475
7.50-15	68.8	5.50	774	215	3890	2850	3425	2570	3190	2395	2450			
					6.00	774	215	3690	2850	3425	2570	3190	2395	2450
					6.50	774	215	3690	2850	3425	2570	3190	2395	2450
7.50-16	75.4	5.50	819	181	3810	3130	3780	2835	3520	2640	2700			
					6.00	819	181	3810	3130	3780	2835	3520	2640	2700
7.50-20	80.0	6.50	935	218	5165	4130	4885	3740	4840	3480	3560			
8.15-15 (28*9-15)	63.0	7.00	706	207	4090	3270	3945	2960	3675	2755	2820			
8.25-12	64.6	6.50	735	206	3328	2660	3215	2410	2955	2245	2295			
8.25-15	68.8	6.50	847	205	4940	3950	4765	3575	4440	3330	3045			
8.25-20	115.0	6.50	902	218	5425	4340	5240	3930	4980	3735	3475			
9.00-16	103.0	6.50	884	218	5135	4110	4965	3725	4825	3470	3550			
9.00-20	123.0	6.50	1038	238	6450	5160	6235	4675	5805	4355	4450			
					7.00	1038	238	6450	5160	6235	4675	5805	4355	4450
10.00-20	186.0	7.50	1073	240	7240	5795	6995	5240	6610	4885	4995			
					8.00	1073	240	7240	5795	6995	5240	6610	4885	4995
11.00-20	186.0	8.00	1075	252	7560	6050	7300	5490	6810	5120	5210			
12.00-20	225.0	8.00	1146	290	8800	7000	8500	6225	8000	6450	6595			
20050-10	24.6	6.50	459	198	2370	1900	2290	1720	2136	1605	1630			
250-15	66.0	7.00	735	220	4366	3400	4220	3160	3930	2955	3010			
					7.50	735	226	4366	3400	4220	3160	3930	2955	3010
300-15	99.0	8.00	838	258	5990	4700	5780	4335	5380	4037	4130			
15x4/12-9	9.6	3.25	380	106	905	725	675	655	805	605	625			
					3.00	380	106	905	725	675	655	805	605	625
16*8-8	14.4	4.33	418	156	1500	1200	1445	1085	1345	1010	1035			
18*7-8	20.8	4.33	457	154	2350	1890	2265	1700	2110	1585	1620			
21*8-9	33.4	6.00	535	188	2810	2250	2715	2035	2530	1895	1940			
23*9-10	46.4	6.50	597	230	4005	3205	3845	2895	3605	2705	2765			
23x10-12	50.0	6.00	595	237	3890	3420	3820	3210	3568	3010	2980			
27*10-12	67.4	6.00	693	235	4465	3570	4315	3235	4020	3015	3080			
28x12.5-15	80.0	6.75	706	300	5735	4590	5540	4165	5170	3890	3955			
32x12.1-15	90.0	9.75	823	301	7120	6700	8860	6170	8410	4520	4910			